acf/settings

- acf/settings
  - Description
  - Changelog
  - Parameters
  - Settings
  - Examples
    - Filter
      - functions.php
    - Function
      - functions.php

acf/settings

Description

Filters the various settings that are used throughout the plugin.

Changelog

- Added in version 5.0.0

Parameters

```
apply_filters( "acf/settings/{$name}", $value );
```

- `$value` *(mixed)* The setting value.

Settings

The following table lists the available settings which can be modified.

Name	Type	Added	Description
`path`	string	5.0.0	Absolute path to ACF plugin folder including trailing slash. Defaults to `plugin_dir_path()`
`url`	string	5.6.8	URL to ACF plugin folder including trailing slash. Defaults to `plugin_dir_url()`
`dir`	string	5.0.0	URL to ACF plugin folder including trailing slash. Defaults to `plugin_dir_url()`. Deprecated in version 5.6.8. Please use **url** instead
`show_admin`	boolean	5.0.0	Show/hide ACF menu item. Defaults to true
`stripslashes`	boolean	5.0.0	Runs the function `stripslashes()` on all $_POST data. Some servers / WP installs may require this extra functionality. Defaults to false
`local`	boolean	5.0.0	Enable/Disable local (PHP/json) fields. Defaults to true
`json`	boolean	5.0.0	Enable/Disable json fields. Defaults to true
`save_json`	string	5.0.0	Absolute path to folder where json files will be created when field groups are saved. Defaults to ‘acf-json’ folder within current theme

Name	Type	Added	Description
`load_json`	array	5.0.0	Array of absolute paths to folders where field group json files can be read. Defaults to an array containing at index 0, the ‘acf-json’ folder within current theme
`default_language`	string	5.0.0	Language code of the default language. Defaults to `''`. If WPML is active, ACF will default this to the WPML default language setting
`current_language`	string	5.0.0	Language code of the current post’s language. Defaults to `''`. If WPML is active, ACF will default this to the WPML current language
`capability`	string	5.1.9	Capability used for ACF post types and if the current user can see the ACF menu item. Defaults to ‘manage_options’.
`show_updates`	boolean	5.2.2	Enable/Disable updates to appear in the installed plugin list and show/hide the ACF updates admin page. Defaults to `true`.
`export_textdomain`	string	5.2.9	Used during the ‘Export to PHP’ feature to wrap strings within the `__()` function. Depreciated in v5.4.4 – please see **l10n_textdomain**
`export_translate`	array	5.3.2	Array of keys used during the ‘Export to PHP’ feature to wrap strings within the `__()` function. Defaults to `array('title', 'label', 'instructions')`. Depreciated in v5.3.4 – please see **l10n_field** and **l10n_field_group**

Name	Type	Added	Description
`autoload`	boolean	5.2.8	Sets the default “autoload” setting used in `add_option()`. This function is used when saving new rows to the wp_options table. Defaults to `false`
`l10n`	boolean	5.3.4	Allows ACF to translate field and field group settings using the `__()` function. Defaults to true. Useful to override translation without modifying the textdomain
`l10n_textdomain`	string	5.3.4	Sets the text domain used when translating field and field group settings. Defaults to `''`. Strings will not be translated if this setting is empty
`l10n_field`	array	5.3.4	An array of settings to translate when loading and exporting a field. Defaults to `array('label', 'instructions')`. Depreciated in v5.3.6 – please see `acf/translate_field` filter
`l10n_field_group`	array	5.3.4	An array of settings to translate when loading and exporting a field group. Defaults to `array('title')`. Depreciated in v5.3.6 – please see `acf/translate_field_group` filter
`google_api_key`	string	5.4.0	Specify a Google Maps API authentication key to prevent usage limits. Defaults to `''`
`google_api_client`	string	5.4.0	Specify a Google Maps API Client ID to prevent usage limits. Not needed if using `google_api_key`. Defaults to `''`
`enqueue_google_maps`	boolean	5.5.0	Allows ACF to enqueue and load the Google Maps API JS library. Defaults to true

Name	Type	Added	Description
`enqueue_select2`	boolean	5.5.0	Allows ACF to enqueue and load the Select2 JS/CSS library. Defaults to true
`select2_version`	numeric	5.5.0	Defines which version of Select2 library to enqueue. Either 3 or 4. Defaults to 4 since ACF 5.6.0
`enqueue_datepicker`	boolean	5.5.0	Allows ACF to enqueue and load the WP datepicker JS/CSS library. Defaults to true
`enqueue_datetimepicker`	boolean	5.5.0	Allows ACF to enqueue and load the datetimepicker JS/CSS library. Defaults to true
`row_index_offset`	numeric	5.5.6	Defines the starting index used in all ‘loop’ and ‘row’ functions. Defaults to 1 (1 is the first row), can be changed to 0 (0 is the first row)
`remove_wp_meta_box`	boolean	5.6.0	Allows ACF to remove the default WP custom fields metabox. Defaults to `true`
`rest_api_enabled`	boolean	5.11	Enables/disables the ACF REST API integration.. Defaults to `true`
`rest_api_format`	string	5.11	Defines how ACF formats field values in the REST API. Defaults to `light`
`rest_api_embed_links`	boolean	5.11	Enables/disables embed links for ACF fields in the REST API. Defaults to `true`
`preload_blocks`	boolean	5.12	Allows ACF to preload the initial render html of ACF Blocks into the block editor. Defaults to `true`

Examples

Filter

This example demonstrates how to modify a setting via the `"acf/settings/{$name}"` filter.

functions.php

```
add_filter('acf/settings/path', 'my_acf_settings_path');
function my_acf_settings_path( $path ) {
    return get_stylesheet_directory() . '/acf/';
}
```

Function

This example demonstrates how to modify a setting via the function `acf_update_setting()`. This function is best used during the `acf/init` action.

functions.php

```
add_action('acf/init', 'my_acf_init');
function my_acf_init() {
    acf_update_setting('show_admin', false);
    acf_update_setting('google_api_key', 'xxx');
}
```

□□□ #1
□ □□□ □□□ 2026-08-29 15:44:03 UTC
□ □□□ □□□ 2026-08-29 15:44:03 UTC