LinkedIn

- Prerequisites
- Set up LinkedIn as an IdP
- Example API configuration

import { Render } from "~/components";

Cloudflare Access allows your users to use LinkedIn as their identity provider (IdP).

Prerequisites

Sign in to your LinkedIn account before continuing. Configuring LinkedIn as a Cloudflare Access IdP requires a LinkedIn account.

Set up LinkedIn as an IdP

To configure LinkedIn as an IdP:

1. Go to the LinkedIn Developer Portal.
2. Select **Create App**.
3. On the **Create an app** page, enter an **App name** for your application.
4. Select a **LinkedIn Page** for your application or select **Create a new LinkedIn page** if you do not have a LinkedIn page.
5. Select **Upload a logo** and upload your company logo image file.
6. Select **API Terms of Use** to read the terms of use, and agree to the terms.
7. Select **Create app**.
8. In the **Products** tab of your LinkedIn application, select **Request Access** next to the **Sign In with LinkedIn using OpenID Connect** option.
9. In the **Auth** tab of your LinkedIn application, find the **Client ID** and **Client Secret**. LinkedIn account settings where you will copy the Client ID and Client Secret
10. In the Cloudflare dashboard, go to **Zero Trust** > **Integrations** > **Identity providers**.
11. Under **Your identity providers**, select **Add new identity provider**.
12. Select **LinkedIn** as your IdP.

13. In the **App ID** field, copy and paste the **Client ID** from step 9. In the **Client secret** field, copy and paste the **Client secret** from step 9.
14. Select **Save**.
15. In the **Auth** tab of your LinkedIn application, go to **OAuth 2.0 settings** and select the pencil icon next to **Authorized redirect URLs for your app**.
16. Enter the following URL:

    ```
    https://<your-team-name>.cloudflareaccess.com/cdn-cgi/access/callback
    ```

To test that your connection is working, go to the Cloudflare dashboard > **Zero Trust** > **Integrations** > **Identity providers** and select **Test** next to your LinkedIn login method.

Example API configuration

```
{
  "config": {
    "client_id": "<your client id>",
    "client_secret": "<your client secret>"
  },
  "type": "linkedin",
  "name": "my example idp"
}
```

□□□ #2
□ □□□ □□□ 2026-11-01 00:55:24 UTC
□ □□□ □□□ 2026-11-01 00:55:25 UTC