rtk-header

- Properties
- Usage Examples
  - Basic Usage
  - With Properties

{/* AUTO-GENERATED FILE. DO NOT EDIT MANUALLY. Any manual changes will be overwritten the next time the docs are generated.

Source: https://github.com/cloudflare/realtimekit-ui/blob/main/packages/core/src/components/rtk-header/rtk-header.tsx Generator: https://github.com/cloudflare/realtimekit-ui/blob/main/scripts/generate-stencil-docs.js

To update this page, edit the component source in the realtimekit-ui repository and submit a pull request against the staging branch; the changes will automatically sync here upon the next release. */}

A component that houses all the header components.

Properties

Property	Type	Required	Default	Description
`config`	`UIConfig1`		`createDefaultConfig()`	Config
`disableRender`	`boolean`		-	Whether to render the default UI
`iconPack`	`IconPack1`		`defaultIconPack`	Icon Pack
`meeting`	`Meeting`		-	Meeting
`size`	`Size`		-	Size
`states`	`States`		-	States
`t`	`RtkI18n`		`useLanguage()`	Language
`variant`	`'solid' | 'boxed'`		-	Variant

Usage Examples

Basic Usage

```
<!-- component.html -->
<rtk-header></rtk-header>
```

With Properties

```
<!-- component.html -->
<rtk-header
 [disableRender]="true"
 [meeting]="meeting"
 size="md">
</rtk-header>
```

□□□ #2
□ □□□ □□□ 2026-11-01 03:20:00 UTC
□ □□□ □□□ 2026-11-01 03:20:01 UTC