rtk-plugin-main

- Properties
- Usage Examples
  - Basic Usage
  - With Properties

{/* AUTO-GENERATED FILE. DO NOT EDIT MANUALLY. Any manual changes will be overwritten the next time the docs are generated.

Source: https://github.com/cloudflare/realtimekit-ui/blob/main/packages/core/src/components/rtk-plugin-main/rtk-plugin-main.tsx Generator: https://github.com/cloudflare/realtimekit-ui/blob/main/scripts/generate-stencil-docs.js

To update this page, edit the component source in the realtimekit-ui repository and submit a pull request against the staging branch; the changes will automatically sync here upon the next release. */}

A component which renders a plugin's UI. The plugin's `component` (an HTMLElement) is placed into this element's light DOM and projected into the shadow DOM layout via a `<slot>`. This ensures external CSS from the consuming application continues to apply to the plugin content.

Properties

Property	Type	Required	Default	Description
`iconPack`	`IconPack`		`defaultIconPack`	Icon pack
`meeting`	`Meeting`		-	Meeting
`plugin`	`RTKPlugin`		-	Plugin
`t`	`RtkI18n`		`useLanguage()`	Language

Usage Examples

Basic Usage

```
<!-- component.html -->
<rtk-plugin-main></rtk-plugin-main>
```

With Properties

```
<!-- component.html -->
<rtk-plugin-main
 [meeting]="meeting"
 [plugin]="rtkplugin">
</rtk-plugin-main>
```

□□□ #2
□ □□□ □□□ 2026-11-01 03:21:51 UTC
□ □□□ □□□ 2026-11-01 03:21:52 UTC