Interface: NavigationIntents

- Container Methods
  - viewContainers
    - Returns
  - viewContainer
    - Parameters
    - Returns
  - viewContainerLogs
    - Parameters
    - Returns
  - viewContainerInspect
    - Parameters
    - Returns
  - viewContainerTerminal
    - Parameters
    - Returns
  - viewContainerStats
    - Parameters
    - Returns
- Images Methods
  - viewImages
    - Returns
  - viewImage
    - Parameters
    - Returns
- Volume Methods
  - viewVolumes
    - Returns
  - viewVolume

- Parameters
- Returns

`Since`

0.2.0

Container Methods

viewContainers

▸ **viewContainers**(): `Promise`<`void`>

Navigate to the **Containers** tab in Docker Desktop.

```
ddClient.desktopUI.navigate.viewContainers()
```

Returns

`Promise`<`void`>

---

viewContainer

▸ **viewContainer**(`id`): `Promise`<`void`>

Navigate to the **Container** tab in Docker Desktop.

```
await ddClient.desktopUI.navigate.viewContainer(id)
```

Parameters

Name	Type	Description
`id`	`string`	The full container id, e.g. `46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`. You can use the `--no-trunc` flag as part of the `docker ps` command to display the full container id.

Returns

`Promise`<`void`>

A promise that fails if the container doesn't exist.

---

viewContainerLogs

▸ **viewContainerLogs**(`id`): `Promise`<`void`>

Navigate to the **Container logs** tab in Docker Desktop.

```
await ddClient.desktopUI.navigate.viewContainerLogs(id)
```

Parameters

Name	Type	Description
`id`	`string`	The full container id, e.g. `46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`. You can use the `--no-trunc` flag as part of the `docker ps` command to display the full container id.

Returns

`Promise`<`void`>

A promise that fails if the container doesn't exist.

---

viewContainerInspect

▸ **viewContainerInspect**(`id`): `Promise`<`void`>

Navigate to the **Inspect container** view in Docker Desktop.

```
await ddClient.desktopUI.navigate.viewContainerInspect(id)
```

Parameters

Name	Type	Description

`id`	`string`	The full container id, e.g. `46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`. You can use the `--no-trunc` flag as part of the `docker ps` command to display the full container id.

Returns

`Promise`<`void`>

A promise that fails if the container doesn't exist.

---

viewContainerTerminal

▸ **viewContainerTerminal**(`id`): `Promise`<`void`>

Navigate to the container terminal window in Docker Desktop.

```
await ddClient.desktopUI.navigate.viewContainerTerminal(id)
```

`Since`

0.3.4

Parameters

Name	Type	Description
`id`	`string`	The full container id, e.g. `46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`. You can use the `--no-trunc` flag as part of the `docker ps` command to display the full container id.

Returns

`Promise`<`void`>

A promise that fails if the container doesn't exist.

---

viewContainerStats

▸ **viewContainerStats**(`id`): `Promise`<`void`>

Navigate to the container stats to see the CPU, memory, disk read/write and network I/O usage.

```
await ddClient.desktopUI.navigate.viewContainerStats(id)
```

Parameters

Name	Type	Description
`id`	`string`	The full container id, e.g. `46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`. You can use the `--no-trunc` flag as part of the `docker ps` command to display the full container id.

Returns

`Promise`<`void`>

A promise that fails if the container doesn't exist.

Images Methods

viewImages

▸ **viewImages**(): `Promise`<`void`>

Navigate to the **Images** tab in Docker Desktop.

```
await ddClient.desktopUI.navigate.viewImages()
```

Returns

`Promise`<`void`>

---

viewImage

▸ **viewImage**(`id`, `tag`): `Promise`<`void`>

Navigate to a specific image referenced by `id` and `tag` in Docker Desktop. In this navigation route you can find the image layers, commands, created time and size.

```
await ddClient.desktopUI.navigate.viewImage(id, tag)
```

Parameters

Name	Type	Description
`id`	`string`	The full image id (including sha), e.g. `sha256:34ab3ae068572f4e85c448b4035e6be5e19cc41f69606535cd4d768a63432673`.
`tag`	`string`	The tag of the image, e.g. `latest`, `0.0.1`, etc.

Returns

`Promise`<`void`>

A promise that fails if the image doesn't exist.

Volume Methods

viewVolumes

▸ **viewVolumes**(): `Promise`<`void`>

Navigate to the **Volumes** tab in Docker Desktop.

```
ddClient.desktopUI.navigate.viewVolumes()
```

Returns

`Promise`<`void`>

---

viewVolume

▸ **viewVolume**(`volume`): `Promise`<`void`>

Navigate to a specific volume in Docker Desktop.

```
await ddClient.desktopUI.navigate.viewVolume(volume)
```

Parameters

Name	Type	Description
`volume`	`string`	The name of the volume, e.g. `my-volume`.

Returns

`Promise`<`void`>

□□□ #2
□ □□□ □□□ 2026-10-31 19:42:09 UTC
□ □□□ □□□ 2026-10-31 19:42:11 UTC