Navigation

- Parameters
- Returns

`ddClient.desktopUI.navigate` enables navigation to specific screens of Docker Desktop such as the containers tab, the images tab, or a specific container's logs.

For example, navigate to a given container logs:

```
const id = '8c7881e6a107';
try {
  await ddClient.desktopUI.navigate.viewContainerLogs(id);
} catch (e) {
  console.error(e);
  ddClient.desktopUI.toast.error(
    `Failed to navigate to logs for container "${id}".`
  );
}
```

Parameters

Name	Type	Description
`id`	`string`	The full container id, e.g. `46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`. You can use the `--no-trunc` flag as part of the `docker ps` command to display the full container id.

Returns

`Promise`<`void`>

A promise that fails if the container doesn't exist.

For more details about all navigation methods, see the Navigation API reference.

> Deprecated navigation methods
>
> These methods are deprecated and will be removed in a future version. Use the methods specified above.

```
window.ddClient.navigateToContainers();
// id - the full container id, e.g.
`46b57e400d801762e9e115734bf902a2450d89669d85881058a46136520aca28`
window.ddClient.navigateToContainer(id);
window.ddClient.navigateToContainerLogs(id);
window.ddClient.navigateToContainerInspect(id);
window.ddClient.navigateToContainerStats(id);

window.ddClient.navigateToImages();
window.ddClient.navigateToImage(id, tag);

window.ddClient.navigateToVolumes();
window.ddClient.navigateToVolume(volume);

window.ddClient.navigateToDevEnvironments();
```

□□□ #2
□ □□□ □□□ 2026-10-31 19:33:11 UTC
□ □□□ □□□ 2026-10-31 19:33:13 UTC