Using Gordon via CLI

- Basic usage
- Working directory
- Disabling Gordon
- Commands

{{< summary-bar feature_name="Gordon" >}}

The `docker ai` command provides a Terminal User Interface (TUI) for Gordon, integrating AI assistance directly into your terminal.

Basic usage

Launch the interactive TUI:

```
$ docker ai
```

This opens Gordon's terminal interface where you can type prompts, approve actions, and continue conversations with full context.

Pass a prompt directly as an argument:

```
$ docker ai "list my running containers"
```

Exit the TUI with `/exit` or `Ctrl+C`.

Working directory

The working directory sets the default context for Gordon's file operations.

Gordon uses your current shell directory as the working directory:

```
$ cd ~/my-project
$ docker ai
```

Override with `-C` or `--working-dir`:

```
$ docker ai -C ~/different-project
```

Disabling Gordon

Gordon CLI is part of Docker Desktop. To disable it, disable Gordon in Docker Desktop Settings:

1. Open Docker Desktop Settings.
2. Navigate to the **AI** section.
3. Clear the **Enable Gordon** option.
4. Select **Apply**.

Commands

The `docker ai` command includes several subcommands:

Interactive mode (default):

```
$ docker ai
```

Opens the TUI for conversational interaction.

Version:

```
$ docker ai version
```

Displays the Gordon version.

Feedback:

```
$ docker ai feedback
```

Opens a feedback form in your browser.

□□□ #2
□ □□□ □□□ 2026-10-31 18:53:33 UTC
□ □□□ □□□ 2026-10-31 18:53:34 UTC