数值的扩展

目录
二进制和八进制表示法
数值分隔符
Number.isFinite(), Number.isNaN() Number.parseInt(), Number.parseFloat() Number.isInteger()
Number.EPSILON
安全整数和 Number.isSafeInteger() Math 对象的扩展
Math.trunc()
Math.sign()
Math.cbrt()
Math.clz32()
Math.imul()
Math.fround()
Math.hypot()
Math.f16round()
对数方法
双曲函数方法
BigInt 数据类型
简介
BigInt 函数
转换规则
数学运算
其他运算

二进制和八进制表示法

ES6 [illegible] `0b` [illegible] `0B` [illegible] `0o` [illegible] `0O` [illegible]

```
0b111110111 === 503 // true
0o767 === 503 // true
```

[illegible] ES5 [illegible] `0` [illegible] ES6 [illegible] `0o` [illegible]

```
// [illegible]
(function(){
  console.log(0o11 === 011);
})() // true

// [illegible]
(function(){
  'use strict';
  console.log(0o11 === 011);
})() // Uncaught SyntaxError: Octal literals are not allowed in strict mode.
```

[illegible] `0b` [illegible] `0o` [illegible] `Number` [illegible]

```
Number('0b111')  // 7
Number('0o10')  // 8
```

[illegible]

[illegible] `1000` [illegible] `1,000` [illegible]

[ES2021](#)[illegible] JavaScript [illegible] `_` [illegible]

```
let budget = 1_000_000_000_000;
budget === 10 ** 12 // true
```

[illegible]

```
123_00 === 12_300 // true

12345_00 === 123_4500 // true
12345_00 === 1_234_500 // true
```

[illegible]

```
// [illegible]
0.000_001


// [illegible]
1e10_000
```

[illegible]

- [illegible] leading[illegible] trailing[illegible]
- [illegible]
- [illegible]
- [illegible] `e` [illegible] `E` [illegible]

[illegible]

```
// [illegible]
3_.141
3._141
1_e12
1e_12
123__456
_1464301
1464301_
```

[illegible]

```
// [illegible]
0b1010_0001_1000_0101
// [illegible]
0xA0_B0_C0
```

[illegible]

[illegible] `0b` [illegible] `0B` [illegible] `0o` [illegible] `0O` [illegible] `0x` [illegible] `0X` [illegible]

```
// [illegible]
0_b111111000
0b_111111000
```

[illegible] JavaScript [illegible]

```
let num = 12_345;


num // 12345
num.toString() // 12345
```

[illegible] `num` [illegible] `12_345` [illegible]

[illegible]
[illegible]

- Number()
- parseInt()
- parseFloat()

```
Number('123_456') // NaN
parseInt('123_456') // 123
```

Number.isFinite(), Number.isNaN()

ES6 [illegible] `Number` [illegible] `Number.isFinite()` [illegible] `Number.isNaN()` [illegible]

`Number.isFinite()` [illegible] finite[illegible] `Infinity` [illegible]

```
Number.isFinite(15); // true
Number.isFinite(0.8); // true
Number.isFinite(NaN); // false
Number.isFinite(Infinity); // false
Number.isFinite(-Infinity); // false
Number.isFinite('foo'); // false
Number.isFinite('15'); // false
Number.isFinite(true); // false
```

[illegible] `Number.isFinite` [illegible] `false` [illegible]

`Number.isNaN()` [illegible] `NaN` [illegible]

```
Number.isNaN(NaN) // true
Number.isNaN(15) // false
Number.isNaN('15') // false
Number.isNaN(true) // false
```

```
Number.isNaN(9/NaN) // true
Number.isNaN('true' / 0) // true
Number.isNaN('true' / 'true') // true
```

□□□□□□□□ `NaN`□ `Number.isNaN`□□□□ `false`□

□□□□□□□□□□ `isFinite()`□ `isNaN()`□□□□□□□□□□□□□□ `Number()` □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ `Number.isFinite()`□□□□□□□□□ `false`, `Number.isNaN()`□□□□ `NaN`□□□ `true`□□ `NaN`□□□□ `false`□

```
isFinite(25) // true
isFinite("25") // true
Number.isFinite(25) // true
Number.isFinite("25") // false

isNaN(NaN) // true
isNaN("NaN") // true
Number.isNaN(NaN) // true
Number.isNaN("NaN") // false
Number.isNaN(1) // false
```

Number.parseInt(), Number.parseFloat()

ES6 □□□□□ `parseInt()`□ `parseFloat()`□□□□ `Number`□□□□□□□□□□□□□□□

```
// ES5□□□
parseInt('12.34') // 12
parseFloat('123.45#') // 123.45

// ES6□□□
Number.parseInt('12.34') // 12
Number.parseFloat('123.45#') // 123.45
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Number.parseInt === parseInt // true
Number.parseFloat === parseFloat // true
```

Number.isInteger()

`Number.isInteger()` □□□□□□□□□□□□□□□□

```
Number.isInteger(25) // true
Number.isInteger(25.1) // false
```

JavaScript □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 25 □ 25.0 □□□□□□□□□

```
Number.isInteger(25) // true
Number.isInteger(25.0) // true
```

□□□□□□□□□ `Number.isInteger` □□ `false` □

```
Number.isInteger() // false
Number.isInteger(null) // false
Number.isInteger('15') // false
Number.isInteger(true) // false
```

□□□□□□ JavaScript □□ IEEE 754 □□□□□□□□□ 64□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 53 □□□□□□ 1 □□□□□ 52 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 54 □□□□□□□□□□□□□□□□□□□□ `Number.isInteger` □□□□□□□

```
Number.isInteger(3.0000000000000002) // true
```

□□□□□□ `Number.isInteger` □□□□□□□□□□□□□□□□□□□□ `true` □□□□□□□□□□□□□□□□□□□□□□□□ 16□□□□□□□□□□□□□□□□□□ 53 □□□□□□□□□□□□□□□ `2` □□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ `Number.MIN_VALUE` □ 5E-324□□□□□ JavaScript □□□□□□□□□□□□□□□□□□ 0□□□□ `Number.isInteger` □□□□□

```
Number.isInteger(5E-324) // false
Number.isInteger(5E-325) // true
```

□□□□□□ `5E-325` □□□□□□□□□□□□□□□□ 0□□□□□ `true` □

[illegible] `Number.isInteger()` [illegible]

Number.EPSILON

ES6 [illegible] `Number` [illegible] `Number.EPSILON` [illegible] 1 [illegible] 1 [illegible]

[illegible] 64 [illegible] 1 [illegible] `1.00..001` [illegible] 51 [illegible] 1 [illegible] 2 [illegible] -52 [illegible]

```
Number.EPSILON === Math.pow(2, -52)
// true
Number.EPSILON
// 2.220446049250313e-16
Number.EPSILON.toFixed(20)
// "0.00000000000000022204"
```

`Number.EPSILON` [illegible] JavaScript [illegible]

[illegible]

```
0.1 + 0.2
// 0.30000000000000004

0.1 + 0.2 - 0.3
// 5.551115123125783e-17

5.551115123125783e-17.toFixed(20)
// '0.00000000000000005551'
```

[illegible] `0.1 + 0.2` [illegible] `0.3` [illegible] `false` [illegible]

```
0.1 + 0.2 === 0.3 // false
```

`Number.EPSILON` [illegible] “[illegible]” [illegible] 2 [illegible] -50 [illegible] `Number.EPSILON * Math.pow(2, 2)` [illegible]

```
5.551115123125783e-17 < Number.EPSILON * Math.pow(2, 2)
// true
```

□□□ `Number.EPSILON` □□□□□□□□□□□□□□□□□□□

```
function withinErrorMargin (left, right) {
  return Math.abs(left - right) < Number.EPSILON * Math.pow(2, 2);
}

0.1 + 0.2 === 0.3 // false
withinErrorMargin(0.1 + 0.2, 0.3) // true

1.1 + 1.3 === 2.4 // false
withinErrorMargin(1.1 + 1.3, 2.4) // true
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□ Number.isSafeInteger()

JavaScript □□□□□□□□□□□□ `-2^53` □ `2^53`
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.pow(2, 53) // 9007199254740992

9007199254740992  // 9007199254740992
9007199254740993  // 9007199254740992

Math.pow(2, 53) === Math.pow(2, 53) + 1
// true
```

□□□□□□□□ 2 □ 53 □□□□□□□□□□□□□□□

ES6 □□□ `Number.MAX_SAFE_INTEGER` □ `Number.MIN_SAFE_INTEGER` □□□□□□□□□□□□□□□□□□□□

```
Number.MAX_SAFE_INTEGER === Math.pow(2, 53) - 1
// true
Number.MAX_SAFE_INTEGER === 9007199254740991
// true

Number.MIN_SAFE_INTEGER === -Number.MAX_SAFE_INTEGER
// true
Number.MIN_SAFE_INTEGER === -9007199254740991
// true
```

[illegible] JavaScript [illegible]

`Number.isSafeInteger()` [illegible]

```
Number.isSafeInteger('a') // false
Number.isSafeInteger(null) // false
Number.isSafeInteger(NaN) // false
Number.isSafeInteger(Infinity) // false
Number.isSafeInteger(-Infinity) // false

Number.isSafeInteger(3) // true
Number.isSafeInteger(1.2) // false
Number.isSafeInteger(9007199254740990) // true
Number.isSafeInteger(9007199254740992) // false

Number.isSafeInteger(Number.MIN_SAFE_INTEGER - 1) // false
Number.isSafeInteger(Number.MIN_SAFE_INTEGER) // true
Number.isSafeInteger(Number.MAX_SAFE_INTEGER) // true
Number.isSafeInteger(Number.MAX_SAFE_INTEGER + 1) // false
```

[illegible]

```
Number.isSafeInteger = function (n) {
  return (typeof n === 'number' &&
    Math.round(n) === n &&
    Number.MIN_SAFE_INTEGER <= n &&
    n <= Number.MAX_SAFE_INTEGER);
}
```

[illegible]
[illegible]

```
Number.isSafeInteger(9007199254740993)
// false
Number.isSafeInteger(990)
// true
Number.isSafeInteger(9007199254740993 - 990)
// true
9007199254740993 - 990
// [illegible] 9007199254740002
// [illegible] 9007199254740003
```

[illegible] `9007199254740993` [illegible] `Number.isSafeInteger` [illegible]
`9007199254740992` [illegible]

```
9007199254740993 === 9007199254740992
// true
```

[illegible]

```
function trusty (left, right, result) {
  if (
    Number.isSafeInteger(left) &&
    Number.isSafeInteger(right) &&
    Number.isSafeInteger(result)
  ) {
    return result;
  }
  throw new RangeError('Operation cannot be trusted!');
}

trusty(9007199254740993, 990, 9007199254740993 - 990)
// RangeError: Operation cannot be trusted!

trusty(1, 2, 3)
// 3
```

Math [illegible]

ES6 [illegible] Math [illegible] 17 [illegible] Math [illegible]

Math.trunc()

`Math.trunc` [illegible]

```
Math.trunc(4.1) // 4
Math.trunc(4.9) // 4
Math.trunc(-4.1) // -4
```

```
Math.trunc(-4.9) // -4
Math.trunc(-0.1234) // -0
```

[illegible] `Math.trunc` [illegible] `Number` [illegible]

```
Math.trunc('123.456') // 123
Math.trunc(true) //1
Math.trunc(false) // 0
Math.trunc(null) // 0
```

[illegible] `NaN` [illegible]

```
Math.trunc(NaN);      // NaN
Math.trunc('foo');    // NaN
Math.trunc();         // NaN
Math.trunc(undefined) // NaN
```

[illegible]

```
Math.trunc = Math.trunc || function(x) {
  return x < 0 ? Math.ceil(x) : Math.floor(x);
};
```

Math.sign()

`Math.sign` [illegible]

[illegible]

- [illegible] `+1` [illegible]
- [illegible] `-1` [illegible]
- [illegible] 0 [illegible] `0` [illegible]
- [illegible] -0 [illegible] `-0`;
- [illegible] `NaN` [illegible]

```
Math.sign(-5) // -1
Math.sign(5) // +1
Math.sign(0) // +0
Math.sign(-0) // -0
Math.sign(NaN) // NaN
```

[illegible] `NaN` [illegible]

```
Math.sign('')  // 0
Math.sign(true)  // +1
Math.sign(false)  // 0
Math.sign(null)  // 0
Math.sign('9')  // +1
Math.sign('foo')  // NaN
Math.sign()  // NaN
Math.sign(undefined)  // NaN
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.sign = Math.sign || function(x) {
  x = +x; // convert to a number
  if (x === 0 || isNaN(x)) {
    return x;
  }
  return x > 0 ? 1 : -1;
};
```

Math.cbrt()

`Math.cbrt()` □□□□□□□□□□□□□□□□

```
Math.cbrt(-1) // -1
Math.cbrt(0)  // 0
Math.cbrt(1)  // 1
Math.cbrt(2)  // 1.2599210498948732
```

□□□□□□ `Math.cbrt()` □□□□□□□□□□ `Number()` □□□□□□□□□□

```
Math.cbrt('8') // 2
Math.cbrt('hello') // NaN
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.cbrt = Math.cbrt || function(x) {
  var y = Math.pow(Math.abs(x), 1/3);
  return x < 0 ? -y : y;
};
```

Math.clz32()

`Math.clz32()` □□□□□□□□ 32 □□□□□□□□□□□□□□□□ 32 □□□□□□□□□□ 0□

```
Math.clz32(0) // 32
Math.clz32(1) // 31
Math.clz32(1000) // 22
Math.clz32(0b01000000000000000000000000000000) // 1
Math.clz32(0b00100000000000000000000000000000) // 2
```

□□□□□□ 0 □□□□□□□□□ 0□□□□ 32 □□□ 0□ 1 □□□□□□□ `0b1` □□□ 1 □□□□ 32 □□□□ 31 □□□ 0□ 1000 □□□□□□□ `0b1111101000` □□□□ 10 □□□□ 32 □□□□ 22 □□□ 0 □

`clz32` □□□□□□□□ ”count leading zero bits in 32-bit binary representation of a number“ □□□□□□□ 32 □□□□□□□□□ 0 □□□□□□□□

□□□□□□ `<<` □□ `Math.clz32` □□□□□□□

```
Math.clz32(0) // 32
Math.clz32(1) // 31
Math.clz32(1 << 1) // 30
Math.clz32(1 << 2) // 29
Math.clz32(1 << 29) // 2
```

□□□□ `Math.clz32` □□□□□□□□□□

```
Math.clz32(3.2) // 30
Math.clz32(3.9) // 30
```

□□□□□□□□□□□ `Math.clz32` □□□□□□□□□□□□□□□□□□

```
Math.clz32() // 32
Math.clz32(NaN) // 32
Math.clz32(Infinity) // 32
Math.clz32(null) // 32
Math.clz32('foo') // 32
Math.clz32([]) // 32
Math.clz32({}) // 32
Math.clz32(true) // 31
```

Math.imul()

`Math.imul` [illegible] 32 [illegible] 32 [illegible]

```
Math.imul(2, 4)   // 8
Math.imul(-1, 8)  // -8
Math.imul(-2, -2) // 4
```

[illegible] 32 [illegible] `Math.imul(a, b)` [illegible] `a * b` [illegible] `(a * b)|0` [illegible] 32 [illegible] JavaScript [illegible] 2 [illegible] 53 [illegible] `Math.imul` [illegible]

```
(0x7fffffff * 0x7fffffff)|0 // 0
```

[illegible] 0 [illegible] 1 [illegible] 1 [illegible] 2 [illegible] 53 [illegible] JavaScript [illegible] 0 [illegible] `Math.imul` [illegible] 1 [illegible]

```
Math.imul(0x7fffffff, 0x7fffffff) // 1
```

Math.fround()

`Math.fround` [illegible] 32 [illegible]

[illegible] 32 [illegible] 24 [illegible] 1 [illegible] 23 [illegible] -2^{24} [illegible] 2^{24} [illegible]

```
Math.fround(0)   // 0
Math.fround(1)   // 1
Math.fround(2 ** 24 - 1)   // 16777215
```

[illegible] 2^{24} [illegible]

```
Math.fround(2 ** 24)       // 16777216
Math.fround(2 ** 24 + 1)   // 16777216
```

`Math.fround` [illegible] 64 [illegible] 32 [illegible] 24 [illegible] 64 [illegible]

```
// □□□□□□□□
Math.fround(1.125) // 1.125
Math.fround(7.25)  // 7.25

// □□□□
Math.fround(0.3)   // 0.30000001192092896
Math.fround(0.7)   // 0.699999988079071
Math.fround(1.0000000123) // 1
```

□□ `NaN` □ `Infinity`□□□□□□□□□□□□□□□□□□□□□□□□ `Math.fround` □□□□□□□□□□□□□□□□□□□□□□□□

```
Math.fround(NaN)      // NaN
Math.fround(Infinity) // Infinity

Math.fround('5')      // 5
Math.fround(true)     // 1
Math.fround(null)     // 0
Math.fround([])       // 0
Math.fround({})       // NaN
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.fround = Math.fround || function (x) {
  return new Float32Array([x])[0];
};
```

Math.hypot()

`Math.hypot` □□□□□□□□□□□□□□□□□□□□

```
Math.hypot(3, 4);        // 5
Math.hypot(3, 4, 5);     // 7.0710678118654755
Math.hypot();            // 0
Math.hypot(NaN);         // NaN
Math.hypot(3, 4, 'foo'); // NaN
Math.hypot(3, 4, '5');   // 7.0710678118654755
Math.hypot(-3);          // 3
```

□□□□□□ 3 □□□□□ 4 □□□□□□ 5 □□□□

□□□□□□□□□ `Math.hypot` □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ NaN□

Math.f16round()

ES2025 □□□ Math.f16round() □□□□□□□□□□□□ 16□□□□□□□□

```
Math.f16round(5) // 5
Math.f16round(5.05) // 5.05078125
```

16□□□□□□□ 16□□□□□□□□□□□□ 5□□□□□□□ 1□□□□□□ 10□□□□□□□□
±65,504 □□□□□□□□□□□□ 1/1024□□□□□□□□□□□□□□□□□□□□□□□□ infinity□

```
Math.f16round(100000) // Infinity
```

□□□□

ES6 □□□ 4 □□□□□□□□

□ 1□ Math.expm1()

`Math.expm1(x)` □□ e^x - 1□□ `Math.exp(x) - 1` □

```
Math.expm1(-1) // -0.6321205588285577
Math.expm1(0)  // 0
Math.expm1(1)  // 1.718281828459045
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.expm1 = Math.expm1 || function(x) {
  return Math.exp(x) - 1;
};
```

□ 2□ Math.log1p()

`Math.log1p(x)` □□□□ `1 + x` □□□□□□□ `Math.log(1 + x)` □□□ `x` □□ -1□□□ `NaN` □

```
Math.log1p(1)  // 0.6931471805599453
Math.log1p(0)  // 0
Math.log1p(-1) // -Infinity
Math.log1p(-2) // NaN
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.log1p = Math.log1p || function(x) {
  return Math.log(1 + x);
};
```

□ 3□ Math.log10()

`Math.log10(x)`□□□□ 10 □□□□ `x`□□□□□□□ `x`□□ 0□□□□ NaN□

```
Math.log10(2)      // 0.3010299956639812
Math.log10(1)      // 0
Math.log10(0)      // -Infinity
Math.log10(-2)     // NaN
Math.log10(100000) // 5
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.log10 = Math.log10 || function(x) {
  return Math.log(x) / Math.LN10;
};
```

□ 4□ Math.log2()

`Math.log2(x)`□□□□ 2 □□□□ `x`□□□□□□□ `x`□□ 0□□□□ NaN□

```
Math.log2(3)       // 1.584962500721156
Math.log2(2)       // 1
Math.log2(1)       // 0
Math.log2(0)       // -Infinity
Math.log2(-2)      // NaN
Math.log2(1024)    // 10
Math.log2(1 << 29) // 29
```

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
Math.log2 = Math.log2 || function(x) {
  return Math.log(x) / Math.LN2;
};
```

□□□□□

ES6 □□□ 6 □□□□□□□□

- `Math.sinh(x)` □□ `x` □□□□□□ hyperbolic sine□
- `Math.cosh(x)` □□ `x` □□□□□□ hyperbolic cosine□
- `Math.tanh(x)` □□ `x` □□□□□□ hyperbolic tangent□
- `Math.asinh(x)` □□ `x` □□□□□□□ inverse hyperbolic sine□
- `Math.acosh(x)` □□ `x` □□□□□□□ inverse hyperbolic cosine□
- `Math.atanh(x)` □□ `x` □□□□□□□ inverse hyperbolic tangent□

BigInt □□□

□□

JavaScript □□□□□□□ 64 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 53 □□□□□□□□ 16 □□□□□□□□□□□□□□□□ JavaScript □□□□□□□□□□ JavaScript □□□□□□□□□□□□□□□□□□□□□□□□□□□□ 2□ 1024□□□□□ JavaScript □□□□□□□□ `Infinity`□

```
// □□ 53 □□□□□□□□□□□□□□□□□
Math.pow(2, 53) === Math.pow(2, 53) + 1 // true

// □□ 2 □ 1024 □□□□□□□□□□
Math.pow(2, 1024) // Infinity
```

ES2020 □□□□□□□□□□ BigInt□□□□□□□□□□□□□□□□ ECMAScript □□□□□□□□ BigInt □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
const a = 2172141653n;
const b = 15346349309n;

// BigInt □□□□□□
a * b // 33334444555566667777n

// □□□□□□□□□□□
Number(a) * Number(b) // 33334444555566670000
```

□□□ Number □□□□□ BigInt □□□□□□□□□□ `n`□

```
1234 // □□□□
1234n // BigInt

// BigInt □□□
1n + 2n // 3n
```

BigInt □□□□□□□□□□□□□□□□□□□□□□□□ `n` □

```
0b1101n // □□□
0o777n // □□□
0xFFn // □□□□
```

BigInt □□□□□□□□□□□□□□□□□□□□□□□□

```
42n === 42 // false
```

`typeof` □□□□□ BigInt □□□□□□□ `bigint` □

```
typeof 123n // 'bigint'
```

BigInt □□□□□□□ `-` □□□□□□□□□□□□ `+` □□□□□□ asm.js □□□

```
-42n // □□
+42n // □□
```

JavaScript □□□□□□ 70□□□□□ `70!` □□□□□□□□□□□□□□□□□□

```
let p = 1;
for (let i = 1; i <= 70; i++) {
  p *= i;
}
console.log(p); // 1.197857166996989e+100
```

□□□ OK□

```
let p = 1n;
for (let i = 1n; i <= 70n; i++) {
  p *= i;
}
console.log(p); // 11978571...00000000n
```

BigInt [illegible]

JavaScript [illegible] `BigInt` [illegible] BigInt [illegible] `Number()` [illegible] BigInt[illegible]

```
BigInt(123) // 123n
BigInt('123') // 123n
BigInt(false) // 0n
BigInt(true) // 1n
```

`BigInt()` [illegible]

```
new BigInt() // TypeError
BigInt(undefined) //TypeError
BigInt(null) // TypeError
BigInt('123n') // SyntaxError
BigInt('abc') // SyntaxError
```

[illegible] `123n` [illegible] Number [illegible]

[illegible]

```
BigInt(1.5) // RangeError
BigInt('1.5') // SyntaxError
```

BigInt [illegible] Object [illegible]

- `BigInt.prototype.toString()`
- `BigInt.prototype.valueOf()`

[illegible] Number [illegible]

- `BigInt.prototype.toLocaleString()`

[illegible]

- `BigInt.asUintN(width, BigInt)`[illegible] BigInt [illegible] 0 [illegible] $2^{width} - 1$ [illegible]
- `BigInt.asIntN(width, BigInt)`[illegible] BigInt [illegible] $-2^{width - 1}$ [illegible] $2^{width - 1} - 1$ [illegible]

```
const max = 2n ** (64n - 1n) - 1n;


BigInt.asIntN(64, max)
// 9223372036854775807n
```

```
BigInt.asIntN(64, max + 1n)
// -9223372036854775808n
BigInt.asUintN(64, max + 1n)
// 9223372036854775808n
```

□□□□□□ `max` □ 64□□□□□ BigInt □□□□□□□□□□□□□□□□ `1n` □ `BigInt.asIntN()` □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ `BigInt.asUintN()` □□□□□□□□□□□□□□□□□□□□□□□□

□□ `BigInt.asIntN()` □ `BigInt.asUintN()` □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
const max = 2n ** (64n - 1n) - 1n;

BigInt.asIntN(32, max) // -1n
BigInt.asUintN(32, max) // 4294967295n
```

□□□□□□ `max` □□□ 64□□ BigInt□□□□□ 32□□□□ 32□□□□□□□

□□□□□□□□ BigInt □□□□□□□ `BigUint64Array` □ `BigInt64Array` □□□□□□□□□□□□□□ 64□ BigInt□ `DataView` □□□□□□□ `DataView.prototype.getBigInt64()` □ `DataView.prototype.getBigUint64()` □□□□□□ BigInt□

□□□

□□□□ `Boolean()` □ `Number()` □ `String()` □□□□□□□ BigInt □□□□□□□□□□□□□□□□□□

```
Boolean(0n) // false
Boolean(1n) // true
Number(1n)  // 1
String(1n)  // "1"
```

□□□□□□□□□□□□□□□□□□□□□□□□□□ `n` □□□□

□□□□□□□□□ `!` □□□□□ BigInt □□□□□□

```
!0n // true
!1n // false
```

□□□

□□□□□□□ BigInt □□□ `+` □ `-` □ `*` □ `**` □□□□□□□□□□ Number □□□□□□□□□□□□□ `/` □□□□□□□□□□□□□□□□

```
9n / 5n
// 1n
```

□□□□□□□□□□□□□□□ BigInt□□□□□□□□□

- □□□□□□□□□□□ `>>>`
- □□□□□□□□ `+`

□□□□□□□□□ BigInt □□□□□□□□□ `>>>` □□□□□□□□□□□□□□ BigInt □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ `>>` □□□□□□□□□□□ `+` □ asm.js □□□□□□ Number □□□□□□□□ asm.js □□□ `+1n` □□□□

BigInt □□□□□□□□□□□□□□□

```
1n + 1.3 // □□
```

□□□□□□□□□□□□□□□ BigInt □ Number□□□□□□□□□□□□□□□ `(2n**53n + 1n) + 0.5` □□□□□□□□□□ BigInt □□□ `0.5` □□□□□□□□□□□□□□□ Number □□□□□□□□□□□ 53 □□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□ Number □□□□□□□□□□□□ BigInt□□□□□□

```
// □□□□□□
Math.sqrt(4n) // □□

// □□□□□□
Math.sqrt(Number(4n)) // 2
```

□□□□□□ `Math.sqrt` □□□□□□□ Number □□□□□□ BigInt □□□□□□□□□□ `Number` □□□□□□□□□□□□□□□□

asm.js □□□ `|0` □□□□□□□□□□□□□□□□ 32□□□□□□□□□ Number □□□□□□□□□□ BigInt □□□ `|0` □□□□□□□□□

```
1n | 0 // □□
```

□□□□

BigInt □□□□□□□□ Number □□□□□□□ `0n` □□□ `false` □□□□□□□ `true` □

```
if (0n) {
  console.log('if');
} else {
  console.log('else');
}
// else
```

□□□□□□ `0n` □□ `false` □□□□□□ `else` □□□

□□□□□□□ `>` □□□□□□□ `==` □□□ BigInt □□□□□□□□□□□□□□□□□□□□□□□□

```
0n < 1 // true
0n < true // true
0n == 0 // true
0n == false // true
0n === 0 // false
```

BigInt □□□□□□□□□□□□□□□□□□□□□□

```
'' + 123n // "123"
```

□□□ #2
□ □□□ □□□ 2020-04-16 10:29:52 UTC
□ □□□ □□□ 2025-10-14 19:46:40 UTC