

Incoming Email



- [Requirements](#)
 - [Configuration](#)
-

Forgejo supports the execution of several actions through incoming mails. This page describes how to set this up.

Requirements

Handling incoming email messages requires an IMAP-enabled email account. The recommended strategy is to use [email sub-addressing](#) but a catch-all mailbox does work too. The receiving email address contains a user/action specific token which tells Forgejo which action should be performed. This token is expected in the `To` and `Delivered-To` header fields.

Forgejo tries to detect automatic responses to skip and the email server should be configured to reduce the incoming noise too (spam, newsletter).

Configuration

To activate the handling of incoming email messages you have to configure the `email.incoming` section in the configuration file.

The `REPLY_TO_ADDRESS` contains the address an email client will respond to. This address needs to contain the `%{token}` placeholder which will be replaced with a token describing the user/action. This placeholder must only appear once in the address and must be in the user part of the address (before the `@`).

An example using email sub-addressing may look like this: `incoming+{%token}@example.com`

If a catch-all mailbox is used, the placeholder may be used anywhere in the user part of the address, for example:

- `incoming+{%token}@example.com`
- `incoming_ {%token}@example.com`

- `%{token}@example.com`
-

[[[#1
[cocobook-sync [[[2026-10-28 16:41:15 UTC
[cocobook-sync [[[2026-10-28 16:41:15 UTC