

Composer Package Registry



- [Requirements](#)
 - [Publish a package](#)
 - [Configuring the package registry](#)
 - [Install a package](#)
-

Publish [Composer](#) packages for your user or organization.

Requirements

To work with the Composer package registry, you can use [Composer](#) to consume and a HTTP upload client like `curl` to publish packages.

Publish a package

To publish a Composer package perform a HTTP PUT operation with the package content in the request body. The package content must be the zipped PHP project with the `composer.json` file.

You cannot publish a package if a package of the same name and version already exists. You must delete the existing package first.

```
PUT https://forgejo.example.com/api/packages/{owner}/composer
```

Parameter	Description
<code>owner</code>	The owner of the package.

If the `composer.json` file does not contain a `version` property, you must provide it as a query parameter:

```
PUT https://forgejo.example.com/api/packages/{owner}/composer?version={x.y.z}
```

Example request using HTTP Basic authentication:

```
curl --user your_username:your_password_or_token \  
      --upload-file path/to/project.zip \  
      https://forgejo.example.com/api/packages/testuser/composer
```

Or specify the package version as query parameter:

```
curl --user your_username:your_password_or_token \  
      --upload-file path/to/project.zip \  
      https://forgejo.example.com/api/packages/testuser/composer?version=1.0.3
```

If you are using 2FA or OAuth use a [personal access token](#) instead of the password.

The server responds with the following HTTP Status codes.

HTTP Status Code	Meaning
201 Created	The package has been published.
400 Bad Request	The package is invalid.
409 Conflict	A package file with the same combination of parameters exists already.

Configuring the package registry

To register the package registry you need to add it to the Composer `config.json` file (which can usually be found under `~/.composer/config.json`):

```
{  
  "repositories": [  
    {  
      "type": "composer",  
      "url": "https://forgejo.example.com/api/packages/{owner}/composer"  
    }  
  ]  
}
```

To access the package registry using credentials, you must specify them in the `auth.json` file as follows:

```
{
  "http-basic": {
    "forgejo.example.com": {
      "username": "{username}",
      "password": "{password}"
    }
  }
}
```

Parameter	Description
<code>owner</code>	The owner of the package.
<code>username</code>	Your Forgejo username.
<code>password</code>	Your Forgejo password or a personal access token.

Install a package

To install a package from the package registry, execute the following command:

```
composer require {package_name}
```

Optional you can specify the package version:

```
composer require {package_name}:{package_version}
```

Parameter	Description
<code>package_name</code>	The package name.
<code>package_version</code>	The package version.

📄 #3

📄 cocobook-sync 📄 2026-10-28 16:38:34 UTC

📄 cocobook-sync 📄 2026-10-29 01:09:31 UTC