

Webhooks



- [Raw event as JSON or FORM payload:](#)
 - [Dedicated integration:](#)
 - [Generic notification messages in chosen channel/chat:](#)
 - [Event information](#)
 - [Example](#)
 - [Authorization header](#)
-

Forgejo supports webhooks for repository events. This can be configured on the settings page `/:username/:reponame/settings/hooks` by a repository admin. Webhooks can also be configured on a per-organization and whole-system basis (default webhooks on repository creation or instance-wide webhooks). The currently supported webhook types are:

Raw event as JSON or FORM payload:

- Forgejo (GET or POST)
- Gitea (GET or POST)
- Gogs (POST)

Dedicated integration:

- Packagist: ask Packagist to refresh the given package
- SourceHut Builds: submit build manifests (only on push)

Generic notification messages in chosen channel/chat:

- Matrix
- Slack
- Discord
- Dingtalk

- Telegram
- Microsoft Teams
- Feishu / Lark Suite
- WeCom (Wechat Work)

These channels don't implement all webhook types. Those types that are implemented have to be manually tested. Try them and open an [issue](#) if they do not work for your use case.

Event information

The following is an example of event information that will be sent by Forgejo to a Payload URL:

```
X-Forgejo-Delivery: f6266f16-1bf3-46a5-9ea4-602e06ead473
X-Forgejo-Event: push
X-GitHub-Delivery: f6266f16-1bf3-46a5-9ea4-602e06ead473
X-GitHub-Event: push
X-Gogs-Delivery: f6266f16-1bf3-46a5-9ea4-602e06ead473
X-Gogs-Event: push
X-Gitea-Delivery: f6266f16-1bf3-46a5-9ea4-602e06ead473
X-Gitea-Event: push
```

```
{
  "ref": "refs/heads/develop",
  "before": "28e1879d029cb852e4844d9c718537df08844e03",
  "after": "bffeb74224043ba2feb48d137756c8a9331c449a",
  "compare_url":
"http://localhost:3000/forgemo/webhooks/compare/28e1879d029cb852e4844d9c718537df08844e03...bff
eb74224043ba2feb48d137756c8a9331c449a",
  "commits": [
    {
      "id": "bffeb74224043ba2feb48d137756c8a9331c449a",
      "message": "Webhooks Yay!",
      "url":
"http://localhost:3000/forgemo/webhooks/commit/bffeb74224043ba2feb48d137756c8a9331c449a",
      "author": {
        "name": "Forgejo",
        "email": "someone@forgejo.org",
        "username": "forgejo"
      },
      "committer": {
```

```
    "name": "Forgejo",
    "email": "someone@forgejo.org",
    "username": "forgejo"
  },
  "timestamp": "2017-03-13T13:52:11-04:00"
}
],
"repository": {
  "id": 140,
  "owner": {
    "id": 1,
    "login": "forgejo",
    "full_name": "Forgejo",
    "email": "someone@forgejo.org",
    "avatar_url": "https://localhost:3000/avatars/1",
    "username": "forgejo"
  },
  "name": "webhooks",
  "full_name": "forgejo/webhooks",
  "description": "",
  "private": false,
  "fork": false,
  "html_url": "http://localhost:3000/forgejo/webhooks",
  "ssh_url": "ssh://forgejo@localhost:2222/forgejo/webhooks.git",
  "clone_url": "http://localhost:3000/forgejo/webhooks.git",
  "website": "",
  "stars_count": 0,
  "forks_count": 1,
  "watchers_count": 1,
  "open_issues_count": 7,
  "default_branch": "master",
  "created_at": "2017-02-26T04:29:06-05:00",
  "updated_at": "2017-03-13T13:51:58-04:00"
},
"pusher": {
  "id": 1,
  "login": "forgejo",
  "full_name": "Forgejo",
  "email": "someone@forgejo.org",
```

```
    "avatar_url": "https://localhost:3000/avatars/1",
    "username": "forgejo"
  },
  "sender": {
    "id": 1,
    "login": "forgejo",
    "full_name": "Forgejo",
    "email": "someone@forgejo.org",
    "avatar_url": "https://localhost:3000/avatars/1",
    "username": "forgejo"
  }
}
```

Example

This is an example of how to use webhooks to run a PHP script upon push requests to the repository. In your repository Settings, under Webhooks, set up a Forgejo webhook as follows:

- Target URL: `http://example.com/webhook.php`
- HTTP Method: POST
- POST Content Type: `application/json`
- Secret: 123
- Trigger On: Push Events
- Active: Checked

Now, on your server, create the PHP file `webhook.php`.

```
<?php

$secret_key = '123';

// check for POST request
if ($_SERVER['REQUEST_METHOD'] != 'POST') {
    error_log('FAILED - not POST - '. $_SERVER['REQUEST_METHOD']);
    exit();
}

// get content type
$content_type = isset($_SERVER['CONTENT_TYPE']) ? strtolower(trim($_SERVER['CONTENT_TYPE'])) :
```

```
if ($content_type != 'application/json') {
    error_log('FAILED - not application/json - '. $content_type);
    exit();
}

// get payload
$payload = trim(file_get_contents("php://input"));

if (empty($payload)) {
    error_log('FAILED - no payload');
    exit();
}

// get header signature
$header_signature = isset($_SERVER['HTTP_X_FORGEJO_SIGNATURE']) ?
$_SERVER['HTTP_X_FORGEJO_SIGNATURE'] : '';

if (empty($header_signature)) {
    error_log('FAILED - header signature missing');
    exit();
}

// calculate payload signature
$payload_signature = hash_hmac('sha256', $payload, $secret_key, false);

// check payload signature against header signature
if ($header_signature !== $payload_signature) {
    error_log('FAILED - payload signature');
    exit();
}

// convert json to array
$decoded = json_decode($payload, true);

// check for json decode errors
if (json_last_error() !== JSON_ERROR_NONE) {
    error_log('FAILED - json decode - '. json_last_error());
    exit();
}
```

```
// success, do something
```

There is a Test Delivery button in the webhook settings that allows testing the configuration as well as a list of the most Recent Deliveries.

Authorization header

Forgejo webhooks can be configured to send an [authorization header](#) to the target.



The screenshot shows the Forgejo webhook configuration interface. It includes radio buttons for "All Events" and "Custom Events...". Below these is a "Branch filter" input field containing an asterisk (*). A note explains that the branch filter is a glob pattern for push, branch creation, and branch deletion events, with examples like "master" or "{master, release*}". Below the branch filter is an "Authorization Header" input field. A note states that this header will be included in requests when present, with examples: "Bearer token123456" and "Basic YWxhZGRpbjpvYVuc2VzYW11". At the bottom, there is a checked checkbox for "Active" with the text "Information about triggered events will be sent to this webhook URL." and a green "Add Webhook" button.

The authentication string is stored encrypted in the database.

❏	#2	
❏	cocobook-sync	❏ 2026-07-26 05:23:37 UTC
❏	cocobook-sync	❏ 2026-07-26 05:23:37 UTC