imap

`imap.folder`
The folder to drop the mails into, which is typically the Drafts folder. For example: `INBOX.Drafts`, `INBOX/Drafts` or `[Gmail]/Drafts`. The IMAP folder to interact with MUST be specified; the value of this configuration variable is used as the fallback default value when the `--folder` option is not given.

`imap.tunnel`
Command used to set up a tunnel to the IMAP server through which commands will be piped instead of using a direct network connection to the server. Required when `imap.host` is not set.

`imap.host`
A URL identifying the server. Use an `imap://` prefix for non-secure connections and an `imaps://` prefix for secure connections. Ignored when `imap.tunnel` is set, but required otherwise.

`imap.user`
The username to use when logging in to the server.

`imap.pass`
The password to use when logging in to the server.

`imap.port`
An integer port number to connect to on the server. Defaults to 143 for `imap://` hosts and 993 for `imaps://` hosts. Ignored when `imap.tunnel` is set.

`imap.sslverify`
A boolean to enable/disable verification of the server certificate used by the SSL/TLS connection. Default is `true`. Ignored when `imap.tunnel` is set.

`imap.preformattedHTML`
A boolean to enable/disable the use of html encoding when sending a patch. An html encoded patch will be bracketed with `<pre>` and have a content type of text/html. Ironically, enabling this option causes Thunderbird to send the patch as a plain/text, format=fixed email. Default is `false`.

`imap.authMethod`
Specify the authentication method for authenticating with the IMAP server. If Git was built with the NO_CURL option, or if your curl version is older than 7.34.0, or if you’re running `git-imap-send` with the `--no-curl` option, the only supported methods are `PLAIN`, `CRAM-MD5`, `OAUTHBEARER` and `XOAUTH2`. If this is not set then `git` `imap-send` uses the basic IMAP plaintext `LOGIN` command.

□□□ #2
□ □□□ □□□ 2026-10-31 20:07:24 UTC
□ □□□ □□□ 2026-10-31 20:07:25 UTC