Attributes

- [redacted]
- [redacted]
- [redacted]
  - attribute [redacted]
  - text source
  - html [redacted]
  - query [redacted]
  - [redacted]
    - [redacted]
- [redacted]
- [redacted]

Block attributes provide information about the data stored by a block. For example, rich content, a list of image URLs, a background color, or a button title.

A block can contain any number of attributes, and these are specified by the `attributes` field - an object where each key is the name of the attribute, and the value is the attribute definition.

The attribute definition will contain, at a minimum, either a `type` or an `enum`. There may be additional fields.

Example: Attributes object defining three attributes - `url`, `title`, and `size`.

```
{
	url: {
		type: 'string',
		source: 'attribute',
		selector: 'img',
		attribute: 'src',
	},
	title: {
		type: 'string',
```

```
},
size: {
enum: [ 'large', 'small' ],
},
}
```

When a block is parsed this definition will be used to extract data from the block content. Anything that matches will be available to your block through the `attributes` prop.

This parsing process can be summarized as:

1. Extract value from the `source`.
2. Check value matches the `type`, or is one of the `enum` values.

Example: Attributes available in the `edit` and function, using the above attributes definition.

```
function YourBlockEdit( { attributes } ) {
return (
<p>URL is { attributes.url }, title is { attributes.title }, and size is { attributes.size
}.</p>
)
}
```

The block is responsible for using the `save` function to ensure that all attributes with a `source` field are saved according to the attributes definition. This is not automatic.

Attributes without a `source` will be automatically saved in the block comment delimiter.

For example, using the above attributes definition you would need to ensure that your `save` function has a corresponding img tag for the `url` attribute. The `title` and `size` attributes will be saved in the comment delimiter.

Example: Example `save` function that contains the `url` attribute.

```
function YourBlockSave( { attributes } ) {
return (
<img src={ attributes.url } />
)
}
```

The saved HTML will contain the `title` and `size` in the comment delimiter, and the `url` in the `img` node.

```
<!-- block:your-block {"title":"hello world","size":"large"} -->
<img src="/image.jpg" />
<!-- /block:your-block -->
```

If an attribute changes over time then a block deprecation can help migrate from an older attribute, or remove it entirely.

□□□□

`type` □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ `source` □□□□□

□□□□□ `enum` □□□ `type` □□□□□ `type` □□□ `enum` □□□□□

`type` □□□□□□□□□□

- `null`
- `boolean`
- `object`
- `array`
- `string`
- `integer`
- `number` □□ `integer` □□□

□□□□ `object` □□□□□□□ `source` □□□□□□□□□□□□□□□ `query` □□□□□

□□□□

□□□□□□□□□□□□□□□□□□□□□□□□ `enum` □□□□□□□□□□□□□□□□□□

□□ □ `enum` □□□

```
{
□size: {
□□enum: [ 'large', 'small', 'tiny' ]
□}
}
```

□□□

□□□

□□□□□

```
{
□url: {
□□type: 'string',
□□source: 'attribute',
□□selector: 'img',
□□attribute: 'src',
□}
}
```

□□□□□□□□

```
{ "url": "https://lorempixel.com/1200/800/" }
```

□□□□□□□□□□□□ `string` □□□ HTML □□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□ □□□□□□□□□□□□ `width` □□□

□□□□□□

```
<div>
□□□

□<img src="https://lorempixel.com/1200/800/" width="50" />
</div>
```

□□□□□

```
{
□width: {
□□type: 'string',
□□source: 'attribute',
□□selector: 'img',
□□attribute: 'width',
□}
}
```

□□□□□□□□

```
{ "width": "50" }
```

□□□□□□□□□□□□□□□□□□□□ `button` □□ `disabled` □□□□□□□□□□□□□□□□ `boolean` □□□□□□□□□□□□□□

□□ □□□□□□□□□□□□ `disabled` □□□

□□□□□□

```
<div>
□□□

□<button type="button" disabled>□□</button>
</div>
```

□□□□□

```
{
□disabled: {
□□type: 'boolean',
□□source: 'attribute',
□□selector: 'button',
□□attribute: 'disabled',
□}
}
```

□□□□□□□□

```
{ "disabled": true }
```

`text` source

Use `text` to extract the inner text from markup. Note that HTML is returned according to the rules of `textContent`.

Example: Extract the `content` attribute from a figcaption element found in the block's markup.

Saved content:

```
<figure>
□<img src="/image.jpg" />

□<figcaption>The inner text of the figcaption element</figcaption>
```

```
</figure>
```

Attribute definition:

```
{
	content: {
		type: 'string',
		source: 'text',
		selector: 'figcaption',
	}
}
```

Attribute available in the block:

```
{ "content": "The inner text of the figcaption element" }
```

Another example, using `text` as the source, and using `.my-content` class as the selector to extract text:

Example: Extract the `content` attribute from an element with `.my-content` class found in the block's markup.

Saved content:

```
<div>
	<img src="/image.jpg" />

	<p class="my-content">The inner text of .my-content class</p>
</div>
```

Attribute definition:

```
{
	content: {
		type: 'string',
		source: 'text',
		selector: '.my-content',
	}
}
```

Attribute available in the block:

```
{ "content": "The inner text of .my-content class" }
```

`html` □

□□ `html` □□□□□□□□ HTML□□□□□□□□□□□□ `innerHTML` □□□□

□□ □□□□□□□□□ figcaption □□□□□ `content` □□□

□□□□□□

```
<figure>
□<img src="/image.jpg" />

□<figcaption>The inner text of the <strong>figcaption</strong> element</figcaption>
</figure>
```

□□□□□

```
{
□content: {
□□type: 'string',
□□source: 'html',
□□selector: 'figcaption',
□}
}
```

□□□□□□□

```
{ "content": "The inner text of the <strong>figcaption</strong> element" }
```

`query` □□

□□ `query` □□□□□□□□□□□□□□□□ `selector` □□□□□□□□□□□□□□□□

```
<div>
  <img src="https://lorempixel.com/1200/800/" alt="large image" />
  <img src="https://lorempixel.com/50/50/" alt="small image" />
</div>
```

□□□□□

```
{
  images: {
    type: 'array',
    source: 'query',
    selector: 'img',
    query: {
      url: {
        type: 'string',
        source: 'attribute',
        attribute: 'src',
      },
      alt: {
        type: 'string',
        source: 'attribute',
        attribute: 'alt',
      },
    }
  }
}
```

□□□□□□□□

```
{
  "images": [
    { "url": "https://lorempixel.com/1200/800/", "alt": "large image" },
    { "url": "https://lorempixel.com/50/50/", "alt": "small image" }
  ]
}
```

□□□□□□□□

>

□□□

□□□□□□□□□□□□□□□□ `register_post_meta` □□□□□□ `single` □ /□ `type` □□□

```
function gutenberg_my_block_init() {
□register_post_meta( 'post', 'author_count', array(
□□'show_in_rest' => true,
□□'single' => true,
□□'type' => 'integer',
□) );
}
add_action( 'init', 'gutenberg_my_block_init' );
```

□□□□□□□□□□□□□□□□□□ `string` □□□□□□□□□ JSON
□□□□□□□□□□□□□□□□□□□□□□ JSON□□□□□□□□□□□□ JSON
□□□

□□□□□□□□□□□□□□□□□□□

```
    { "url": "https://lorempixel.com/50/50/", "alt": "small image" }
]
}
```

```
{
type: 'object',
default: {
width: 100,
title: 'title'
}
}
```


`role`

 `content` `content`
 `local` `local`

 `content`

```
{
    content: {
        type: 'string',
        source: 'html',
        selector: 'p',
        role: 'content',
    }
}
```

 `local`

```
{
    blob: {
        type: 'string',
        role: 'local',
    }
```

```
}
```

□□□□□□□□□□ WordPress 6.7 □□□□ □

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:43 UTC
□ □□□ □□□ 2026-03-26 17:08:43 UTC