

add-icon



- [SVG framework function: addIcon](#)
 - [Usage](#)
 - [Examples](#)
 - [Notes](#)
 - [API provider](#)
 - [One icon](#)
-

```
title: 'Iconify SVG Framework Function: addIcon'
types:
  IconifyJSON: '/docs/types/iconify-json.md'
  IconifyIcon: '/docs/types/iconify-icon.md'
functions:
  addCollection: './add-collection.md'
```

SVG framework function: addIcon

This tutorial is part of [Iconify SVG Framework functions tutorial](#).

```
include: icon-components/functions/add-icon/intro
replacements:
  - search: component
    replace: SVG framework
```

Usage

```
include icon-components/functions/add-icon/props
```

Examples

```
Iconify.addIcon('mdi:account-box', {  
  body: '<path d="M6 17c0-2 4-3.1 6-3.1s6 1.1 6 3.1v1H6m9-9a3 3 0 0 1-3 3a3 3 0 0 1-3-3a3 3 0 0 1 3-3a3 3 0 0 1 3 3M3 5v14a2 2 0 0 0 2 2h14a2 2 0 0 0 2-2V5a2 2 0 0 0-2-2H5a2 2 0 0 0-2 2z"  
  fill="currentColor"/>',  
  width: 24,  
  height: 24,  
});
```

Notes

- Icons added by this function are not cached in `[prop]localStorage` and `[prop]sessionStorage`.
- Calling this function will trigger re-scan of DOM on the next tick.

API provider

```
include icon-components/functions/add-icon/provider
```

Example:

```
Iconify.addIcon('@custom:md:test', {  
  body: '<path d="M10 20v-6h4v6h5v-8h3L12 3L2 12h3v8h5z" fill="currentColor"/>',  
  width: 24,  
  height: 24,  
});
```

Code above adds the following icon:

- `[prop]provider` is `[str]custom`.
- `[prop]prefix` is `[str]md`.
- `[prop]name` is `[str]test`.

In HTML code this icon can be used like this:

include icon-components/functions/add-icon/custom

One icon

include icon-components/functions/add-icon/footer

<div><div></div><div></div></div>	#2	
<div><div></div><div></div></div>	<div><div></div><div></div></div>	2026-10-31 14:19:59 UTC
<div><div></div><div></div></div>	<div><div></div><div></div></div>	2026-10-31 14:20:00 UTC