set-variation

- setVariation()
  - Variation
  - Usage
  - Example


```
title: Add icon variation to icon set
types:
  IconSet: './index.md'
  IconifyIcon: '/docs/types/iconify-icon.md'
  ResolvedIconifyIcon: '../iconify-icon.md'
  CommonIconProps: './entries.md#common'
functions:
  setIcon: './set-icon.md'
  setVariation: './set-variation.md'
  setAlias: './set-alias.md'
```

setVariation()

This function is part of `[type]IconSet` class in Iconify Tools.

Function `[func]setVariation()` adds new icon variation to icon set or overwrites existing item.

Variation

Icon variation is an item that is based on different icon, but has at least one transformation applied to it.

For example, `[str]arrow-left` can be a variation of `[str]arrow-right` with `[prop]hFlip` enabled.

Variations make it easier to maintain icons that are based on other icons and reduce content duplication.

Usage

Function has the following parameters:

- `[prop]name`, `[type]string`. Icon name.
- `[prop]parent`, `[type]string`. Parent item name.
- `[prop]props`, `[type]CommonIconProps`. Icon transformations.

Function returns a simple `true` on success, `false` on failure.

Example

```
src: libraries/tools/icon-set/set-alias.ts
title: 'example.ts'
extra:
  - src: libraries/tools/icon-set/set-alias.json
    title: 'Result:'
```

□□□ #2
□ □□□ □□□ 2026-10-31 14:25:35 UTC
□ □□□ □□□ 2026-10-31 14:25:36 UTC