Document: enableStyleSheetsForSet() method

- Syntax
  - Parameters
  - Return value
- Notes
- Examples
- Specifications
- Browser compatibility
- See also

Enables the style sheets matching the specified name in the current style sheet set, and disables all other style sheets (except those without a title, which are always enabled).

Syntax

```
enableStyleSheetsForSet(name)
```

Parameters

- `name`
  - : The name of the style sheets to enable. All style sheets with a title that match this name will be enabled, while all others that have a title will be disabled. Specify an empty string for the *name* parameter to disable all alternate and preferred style sheets (but not the persistent style sheets; that is, those with no `title` attribute).

Return value

None (undefined).

Notes

- Title matches are case-sensitive.
- Calling this method with a `null` *name* has no effect; if you want to disable all alternate and preferred style sheets, you **must** pass "", the empty string.
- Stylesheets that don't have a title are never affected by this method.
- This method never affects the values of document.lastStyleSheetSet or document.preferredStyleSheetSet.

Examples

```
document.enableStyleSheetsForSet("Some style sheet set name");
```

Specifications

Not part of any specification.

Browser compatibility

See also

- Stylesheet
- Document.styleSheets
- document.lastStyleSheetSet
- document.preferredStyleSheetSet
- document.selectedStyleSheetSet

□□□ #3
□ □□□ □□□ 2026-10-31 03:27:53 UTC
□ cocobook-sync □□□ 2026-11-04 17:33:43 UTC