Radio

- Screenshots
- Settings
- Data
- Template usage

import Screenshots from '@site/src/components/Screenshots';

The radio field creates a simple list of radio inputs where you can select a single choice from the predefined list.

Screenshots

<Screenshots name="radio" col1={[['/screenshots/radio-1.png', 'Radio choices inline'], ['/screenshots/radio-2.png', 'Radio choices on multiple lines'],]} />

Settings

Besides the common settings, this field has the following specific settings, the keys are for use with code:

Name	Key	Description
Choices	`options`	List of choices, each per line. If you need to set values and labels, use the format "value: Label" for each choice. When using with code, this setting is an array of `'value' => 'Label'`.
Inline	`inline`	Display choices on a single line? `true` or `false`.

This is a sample field settings array when creating this field with code:

```
[
    'name'    => 'Radio',
    'id'      => 'radio',
    'type'    => 'radio',
    'inline'  => false,
    'options' => [
        'value1' => 'Label1',
        'value2' => 'Label2',
    ],
],
```

Data

This field saves a single selected value in the database.

If the field is cloneable, then the value is stored as a serialized array in a single row in the database.

:::warning

Note that this field stores the **values**, not labels.

:::

Template usage

Displaying the selected value:

```
<?php $value = rwmb_meta( 'my_field_id' ); ?>
<p>Selected: <?= $value ?></p>
```

Displaying the selected label:

```
<p>My choice: <?php rwmb_the_value( 'my_field_id' ) ?></p>
```

Displaying both value and label:

```
<?php
$field   = rwmb_get_field_settings( 'my_field_id' );
```

```
$options = $field['options'];
$value   = rwmb_meta( 'my_field_id' );
?>

Value: <?= $value ?><br>
Label: <?= $options[ $value ] ?>
```

□□□ #2
□ □□□ □□□ 2026-08-29 15:36:17 UTC
□ □□□ □□□ 2026-08-29 15:36:17 UTC