get-proto-info

mysqli::$protocol_version

mysqli_get_proto_info

Returns the version of the MySQL protocol used

ENTITY

ENTITY

int

mysqli-ENTITYprotocol_version

ENTITY

int

mysqli_get_proto_info

mysqli

mysql

Returns an integer representing the MySQL protocol version used by the connection represented by the `mysql` parameter.

ENTITY

ENTITY

Returns an integer representing the protocol version.

ENTITY

`$mysqli-ENTITYprotocol_version` example

ENTITY

```
<?php

mysqli_report(MYSQLI_REPORT_ERROR | MYSQLI_REPORT_STRICT);
$mysqli = new mysqli("localhost", "my_user", "my_password");

/* print protocol version */
printf("Protocol version: %d\n", $mysqli->protocol_version);
```

ENTITY

```
<?php

mysqli_report(MYSQLI_REPORT_ERROR | MYSQLI_REPORT_STRICT);
$link = mysqli_connect("localhost", "my_user", "my_password");

/* print protocol version */
printf("Protocol version: %d\n", mysqli_get_proto_info($link));
```

ENTITY

```
Protocol version: 10
```

ENTITY

`mysqli_get_host_info`

□□□ #2
□ □□□ □□□ 2026-10-31 17:56:17 UTC
□ □□□ □□□ 2026-10-31 17:56:18 UTC