mysqli_driver

ENTITY

The `mysqli_driver` class is an instance of the monostate pattern, i.e. there is only one driver which can be accessed through an arbitrary amount of `mysqli_driver` instances.

ENTITY

final

mysqli_driver

ENTITY

public

readonly

string

client_info

public

readonly

int

client_version

public

readonly

int

driver_version

public

int

report_mode

ENTITY

`client_info`
The Client API header version

`client_version`
The Client version

`driver_version`
The MySQLi Driver version

> This property has been *deprecated* as of PHP 8.1.0. Relying on this property is highly discouraged.

`embedded`
Whether MySQLi Embedded support is enabled

> This property has been *removed* as of PHP 8.0.0.

`reconnect`
Allow or prevent reconnect (see the mysqli.reconnect INI directive)

> This property has been *removed* along with the mysqli.reconnect INI directive as of PHP 8.2.0.

`report_mode`
Set to `MYSQLI_REPORT_OFF`, `MYSQLI_REPORT_ALL` or any combination of `MYSQLI_REPORT_STRICT` (throw Exceptions for errors), `MYSQLI_REPORT_ERROR` (report errors) and `MYSQLI_REPORT_INDEX` (errors regarding indexes). See also `mysqli_report`.

ENTITY

ENTITY	ENTITY
8.2.0	mysqli_driver::$reconnect was removed.
8.1.0	mysqli_driver::$driver_version has been deprecated.
8.0.0	mysqli_driver::$embedded was removed.
7.4.0	mysqli_driver::embedded_server_start and mysqli_driver:embedded_server_end were removed.

ENTITY

□□□ #2
□ □□□ □□□ 2026-10-31 17:57:41 UTC
□ □□□ □□□ 2026-10-31 17:57:43 UTC