servers

- SAPI options

SAPI options

The following list contains the available SAPIENTITYs (`Server Application Programming Interface`) for PHP.

`--with-apxs[=FILE]`
Build shared Apache module. FILE is the optional pathname to the Apache apxs tool; defaults to apxs. Make sure you specify the version of apxs that is actually installed on your system and NOT the one that is in the apache source tarball.

`--with-apache[=DIR]`
Build a static Apache module. DIR is the top-level Apache build directory, defaults to `/usr/local/apache`.

`--with-mod_charset`
Enable transfer tables for mod_charset (Russian Apache).

`--with-apxs2[=FILE]`
Build shared Apache 2.0 module. FILE is the optional pathname to the Apache apxs tool; defaults to apxs.

`--disable-cli`
Disable building the CLI version of PHP (this forces --without-pear). More information is available in the section about Using PHP from the command line.

`--enable-phpdbg`
Enable phpdbg interactive debugger SAPI module support.

`--enable-embed[=TYPE]`
Enable building of the embedded SAPI library. TYPE is either `shared` or `static`, which defaults to `shared`.

`--with-servlet[=DIR]`
Include servlet support. DIR is the base install directory for the JSDK. This SAPI requires the java extension must be built as a shared dl.

`--disable-cgi`
Disable building CGI version of PHP.

This argument also enables FastCGI.

□□□ #2
□ □□□ □□□ 2026-10-31 17:31:55 UTC
□ □□□ □□□ 2026-10-31 17:31:56 UTC