

drop_transform



- [Description](#)
 - [Parameters](#)
 - [Examples](#)
 - [Compatibility](#)
 - [See Also](#)
-

DROP TRANSFORM

DROP TRANSFORM

7

SQL - Language Statements

DROP TRANSFORM

remove a transform

DROP TRANSFORM [IF EXISTS] FOR

type_name

LANGUAGE

lang_name

[CASCADE | RESTRICT]

Description

`DROP TRANSFORM` removes a previously defined transform.

To be able to drop a transform, you must own the type and the language. These are the same privileges that are required to create a transform.

Parameters

IF EXISTS

Do not throw an error if the transform does not exist. A notice is issued in this case.

<type_name>

The name of the data type of the transform.

<lang_name>

The name of the language of the transform.

CASCADE

Automatically drop objects that depend on the transform, and in turn all objects that depend on those objects (see [???](#)).

RESTRICT

Refuse to drop the transform if any objects depend on it. This is the default.

Examples

To drop the transform for type `hstore` and language `plpython3u`:

```
DROP TRANSFORM FOR hstore LANGUAGE plpython3u;
```

Compatibility

This form of `DROP TRANSFORM` is a PostgreSQL extension. See [???](#) for details.

See Also

👤 #2

🕒 2026-10-31 14:11:59 UTC

🕒 2026-10-31 14:12:00 UTC