

`!linecache` --- Random access to text lines

linecache

Source code: `Lib/linecache.py`

The `!linecache` module allows one to get any line from a Python source file, while attempting to optimize internally, using a cache, the common case where many lines are read from a single file. This is used by the `traceback` module to retrieve source lines for inclusion in the formatted traceback.

The `tokenize.open` function is used to open files. This function uses `tokenize.detect_encoding` to get the encoding of the file; in the absence of an encoding token, the file encoding defaults to UTF-8.

The `!linecache` module defines the following functions:

`getline(filename, lineno, module_globals=None)`

Get line *lineno* from file named *filename*. This function will never raise an exception --- it will return `''` on errors (the terminating newline character will be included for lines that are found).

triple: module; search; path

If *filename* indicates a frozen module (starting with `'<frozen '`), the function will attempt to get the real file name from `module_globals['__file__']` if *module_globals* is not `None`.

If a file named *filename* is not found, the function first checks for a `302` `__loader__` in *module_globals*. If there is such a loader and it defines a `get_source` method, then that determines the source lines (if `get_source()` returns `None`, then `''` is returned). Finally, if *filename* is a relative filename, it is looked up relative to the entries in the module search path, `sys.path`.

3.14

Support *filename* of frozen modules.

`clearcache()`

Clear the cache. Use this function if you no longer need lines from files previously read using `getline`.

`checkcache(filename=None)`

Check the cache for validity. Use this function if files in the cache may have changed on disk, and you require the updated version. If *filename* is omitted, it will check all the entries in the cache.

`lazycache(filename, module_globals)`

Capture enough detail about a non-file-based module to permit getting its lines later via `getline` even if *module_globals* is `None` in the later call. This avoids doing I/O until a line is actually needed, without having to carry the module globals around indefinitely.

3.5

Example:

```
>>> import linecache
>>> linecache.getline(linecache.__file__, 8)
'import sys\n'
```

```
### #2
[] [] [] 2026-10-31 17:13:40 UTC
[] [] [] 2026-10-31 17:13:41 UTC
```