Pending removal in future versions

The following APIs are deprecated and will be removed, although there is currently no date scheduled for their removal.

- `Py_TPFLAGS_HAVE_FINALIZE`: Unneeded since Python 3.8.
- `PyErr_Fetch`: Use `PyErr_GetRaisedException` instead.
- `PyErr_NormalizeException`: Use `PyErr_GetRaisedException` instead.
- `PyErr_Restore`: Use `PyErr_SetRaisedException` instead.
- `PyOS_AfterFork`: Use `PyOS_AfterFork_Child` instead.
- `PySlice_GetIndicesEx`: Use `PySlice_Unpack` and `PySlice_AdjustIndices` instead.
- `PyUnicode_READY`: Unneeded since Python 3.12
- `!PyErr_Display`: Use `PyErr_DisplayException` instead.
- `!_PyErr_ChainExceptions`: Use `!_PyErr_ChainExceptions1` instead.
- `!PyBytesObject.ob_shash` member: call `PyObject_Hash` instead.
- Thread Local Storage (TLS) API:
  - `PyThread_create_key`: Use `PyThread_tss_alloc` instead.
  - `PyThread_delete_key`: Use `PyThread_tss_free` instead.
  - `PyThread_set_key_value`: Use `PyThread_tss_set` instead.
  - `PyThread_get_key_value`: Use `PyThread_tss_get` instead.
  - `PyThread_delete_key_value`: Use `PyThread_tss_delete` instead.
  - `PyThread_ReInitTLS`: Unneeded since Python 3.7.

□□□ #2
□ □□□ □□□ 2026-10-31 16:55:52 UTC
□ □□□ □□□ 2026-10-31 16:55:54 UTC