Acf Field Functions Global Functions

- acf_get_field()
- acf_get_raw_field()
- acf_get_field_post()
- acf_is_field_key()
- acf_validate_field()
- acf_get_valid_field()
- acf_translate_field()
- acf_get_fields()
- acf_get_raw_fields()
- acf_get_field_count()
- acf_clone_field()
- acf_prepare_field()
- acf_render_fields()
- acf_render_field_wrap()
- acf_render_field()
- acf_render_field_label()
- acf_get_field_label()
- acf_render_field_instructions()
- acf_render_field_setting()
- acf_update_field()
- _acf_apply_unique_field_slug()
- acf_flush_field_cache()
- acf_delete_field()
- acf_trash_field()
- acf_untrash_field()
- _acf_untrash_field_post_status()

- acf_prefix_fields()
- acf_get_sub_field()
- acf_search_fields()
- acf_is_field()
- acf_get_field_ancestors()
- acf_duplicate_fields()
- acf_duplicate_field()
- acf_prepare_fields_for_export()
- acf_prepare_field_for_export()
- acf_prepare_fields_for_import()
- acf_prepare_field_for_import()
- acf_get_field_json_schema()

---

acf_get_field()

acf_get_field

- Retrieves a field for the given identifier.
- @date 17/1/19
- @since ACF 5.7.10
- @param (int|string) $id The field ID, key or name.
- @return (array|false) The field array.

acf_get_raw_field()

acf_get_raw_field

- Retrieves raw field data for the given identifier.
- @date 18/1/19
- @since ACF 5.7.10
- @param (int|string) $id The field ID, key or name.
- @return (array|false) The field array.

acf_get_field_post()

acf_get_field_post

- Retrieves the field's WP_Post object.
- @date 18/1/19
- @since ACF 5.7.10
- @param (int|string) $id The field ID, key or name.
- @return (array|false) The field array.

`acf_is_field_key()`

acf_is_field_key

- Returns true if the given identifier is a field key.
- @date 6/12/2013
- @since ACF 5.0.0
- @param string $id The identifier.
- @return boolean

`acf_validate_field()`

acf_validate_field

- Ensures the given field valid.
- @date 18/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @return array

`acf_get_valid_field()`

acf_get_valid_field

- Ensures the given field valid.
- @date 28/09/13
- @since ACF 5.0.0
- @param array $field The field array.
- @return array

`acf_translate_field()`

acf_translate_field

- Translates a field's settings.
- @date 8/03/2016
- @since ACF 5.3.2
- @param array $field The field array.
- @return array

`acf_get_fields()`

acf_get_fields

- Returns and array of fields for the given $parent.
- @date 30/09/13
- @since ACF 5.0.0
- @param (int|string|array) $parent The field group or field settings. Also accepts the field group ID or key.
- @return array

`acf_get_raw_fields()`

acf_get_raw_fields

- Returns and array of raw field data for the given parent id.
- @date 18/1/19
- @since ACF 5.7.10
- @param integer $id The field group or field id.
- @return array

`acf_get_field_count()`

acf_get_field_count

- Return the number of fields for the given field group.
- @date 17/10/13
- @since ACF 5.0.0
- @param array $parent The field group or field array.
- @return integer

acf_clone_field()

acf_clone_field

- Allows customization to a field when it is cloned. Used by the clone field.
- @date 8/03/2016
- @since ACF 5.3.2
- @param array $field The field being cloned.
- @param array $clone_field The clone field.
- @return array

acf_prepare_field()

acf_prepare_field

- Prepare a field for input.
- @date 20/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @return array

acf_render_fields()

acf_render_fields

- Renders an array of fields. Also loads the field's value.
- @date 8/10/13
- @since ACF 5.0.0
- @since ACF 5.6.9 Changed parameter order.
- @param array $fields An array of fields.
- @param (int|string) $post_id The post ID to load values from.
- @param string $element The wrapping element type.
- @param string $instruction The instruction render position (label|field).
- @return void

acf_render_field_wrap()

Render the wrapping element for a given field.

- @since ACF 5.0.0
- @param array $field The field array.
- @param string $element The wrapping element type.
- @param string $instruction The instruction render position (label|field).
- @param boolean $field_setting If a field setting is being rendered.
- @return void

acf_render_field()

acf_render_field

- Render the input element for a given field.
- @date 21/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @return void

acf_render_field_label()

acf_render_field_label

- Renders the field's label.
- @date 19/9/17
- @since ACF 5.6.3
- @param array $field The field array.
- @return void

acf_get_field_label()

acf_get_field_label

- Returns the field's label with appropriate required label.
- @date 4/11/2013
- @since ACF 5.0.0
- @param array $field The field array.
- @param string $context The output context (admin).
- @return string The field label in HTML format.

acf_render_field_instructions()

Renders the field's instructions.

- @since ACF 5.6.3
- @param array $field The field array.
- @param boolean $tooltip If the instructions are being rendered as a tooltip.
- @return void

acf_render_field_setting()

acf_render_field_setting

- Renders a field setting used in the admin edit screen.
- @date 21/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @param array $setting The settings field array.
- @param boolean $global Whether this setting is a global or field type specific one.
- @return void

acf_update_field()

acf_update_field

- Updates a field in the database.
- @date 21/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @param array $specific An array of specific field attributes to update.
- @return array

_acf_apply_unique_field_slug()

_acf_apply_unique_field_slug

- Allows full control over 'acf-field' slugs.
- @date 21/1/19
- @since ACF 5.7.10
- @param string $slug The post slug.
- @param integer $post_ID Post ID.
- @param string $post_status The post status.

- @param string $post_type Post type.
- @param integer $post_parent Post parent ID
- @param string $original_slug The original post slug.

`acf_flush_field_cache()`

acf_flush_field_cache

- Deletes all caches for this field.
- @date 22/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @return void

`acf_delete_field()`

acf_delete_field

- Deletes a field from the database.
- @date 21/1/19
- @since ACF 5.7.10
- @param (int|string) $id The field ID, key or name.
- @return boolean True if field was deleted.

`acf_trash_field()`

acf_trash_field

- Trashes a field from the database.
- @date 2/10/13
- @since ACF 5.0.0
- @param (int|string) $id The field ID, key or name.
- @return boolean True if field was trashed.

`acf_untrash_field()`

acf_untrash_field

- Restores a field from the trash.

- @date 2/10/13
- @since ACF 5.0.0
- @param (int|string) $id The field ID, key or name.
- @return boolean True if field was trashed.

`_acf_untrash_field_post_status()`

Filter callback which returns the previous post_status instead of "draft" for the "acf-field" post type.

- Prior to WordPress 5.6.0, this filter was not needed as restored posts were always assigned their original status.
- @since ACF 5.9.5
- @param string $new_status The new status of the post being restored.
- @param integer $post_id The ID of the post being restored.
- @param string $previous_status The status of the post at the point where it was trashed.
- @return string.

`acf_prefix_fields()`

acf_prefix_fields

- Changes the prefix for an array of fields by reference.
- @date 5/9/17
- @since ACF 5.6.0
- @param array $fields An array of fields.
- @param string $prefix The new prefix.
- @return void

`acf_get_sub_field()`

acf_get_sub_field

- Searches a field for sub fields matching the given selector.
- @date 21/1/19
- @since ACF 5.7.10
- @param (int|string) $id The field ID, key or name.
- @param array $field The parent field array.
- @return (array|false)

acf_search_fields()

acf_search_fields

- Searches an array of fields for one that matches the given identifier.
- @date 12/2/19
- @since ACF 5.7.11
- @param (int|string) $id The field ID, key or name.
- @param array $haystack The array of fields.
- @return (int|false)

acf_is_field()

acf_is_field

- Returns true if the given params match a field.
- @date 21/1/19
- @since ACF 5.7.10
- @param array $field The field array.
- @param mixed $id An optional identifier to search for.
- @return boolean

acf_get_field_ancestors()

acf_get_field_ancestors

- Returns an array of ancestor field ID's or keys.
- @date 22/06/2016
- @since ACF 5.3.8
- @param array $field The field array.
- @return array

acf_duplicate_fields()

acf_duplicate_fields

- Duplicate an array of fields.
- @date 16/06/2014
- @since ACF 5.0.0

- @param array $fields An array of fields.
- @param integer $parent_id The new parent ID.
- @return array

acf_duplicate_field()

acf_duplicate_field

- Duplicates a field.
- @date 16/06/2014
- @since ACF 5.0.0
- @param (int|string) $id The field ID, key or name.
- @param integer $parent_id The new parent ID.
- @return boolean True if field was duplicated.

acf_prepare_fields_for_export()

acf_prepare_fields_for_export

- Returns a modified array of fields ready for export.
- @date 11/03/2014
- @since ACF 5.0.0
- @param array $fields An array of fields.
- @return array

acf_prepare_field_for_export()

acf_prepare_field_for_export

- Returns a modified field ready for export.
- @date 11/03/2014
- @since ACF 5.0.0
- @param array $field The field array.
- @return array

acf_prepare_fields_for_import()

acf_prepare_field_for_import

- Returns a modified array of fields ready for import.
- @date 11/03/2014
- @since ACF 5.0.0
- @param array $fields An array of fields.
- @return array

acf_prepare_field_for_import()

acf_prepare_field_for_import

- Returns a modified field ready for import. Allows parent fields to modify themselves and also return sub fields.
- @date 11/03/2014
- @since ACF 5.0.0
- @param array $field The field array.
- @return array

acf_get_field_json_schema()

Retrieves the JSON schema for a field.

- @since 6.8.0
- @param string $field_type The field to get the JSON schema for.
- @return array

□□□ #2
□ □□□ □□□ 2026-08-29 22:50:46 UTC
□ □□□ □□□ 2026-08-29 22:50:46 UTC