systemd-clonesetup

- Description
- See Also

systemd

systemd-clonesetup

8

systemd-clonesetup

systemd-clonesetup@.service

Set up and tear down dm-clone devices

systemd-clonesetup

add

NAME

SOURCE-DEVICE

DEST-DEVICE

META-DEVICE

OPTIONS

systemd-clonesetup

remove

NAME

`systemd-clonesetup@.service`

Description

`systemd-clonesetup` is used to set up (with `add`) and tear down (with `remove`) dm-clone devices. It is primarily used via `systemd-clonesetup@.service` units generated from `/etc/clonetab` by `systemd-clonesetup-generator(8)`.

The positional arguments `NAME`, `SOURCE-DEVICE`, `DEST-DEVICE`, `META-DEVICE`, and `OPTIONS` have the same meaning as the fields in `clonetab(5)`.

Currently, the supported option in `OPTIONS` is `region-size=`<BYTES>, where <BYTES> is measured in bytes (standard suffixes like `K`, `M`, `G` are supported).

See Also

`systemd(1)`, `clonetab(5)`, `systemd-clonesetup-generator(8)`, `systemd.generator(7)`, `dmsetup(8)`

□□□ #1
□ □□□ □□□ 2026-10-31 14:59:32 UTC
□ □□□ □□□ 2026-10-31 14:59:32 UTC