udev_list_entry

- Return Value
- History
- See Also

systemd

udev_list_entry

3

udev_list_entry

udev_list_entry_get_next

udev_list_entry_get_by_name

udev_list_entry_get_name

udev_list_entry_get_value

Iterate and access udev lists

#include <libudev.h>

struct udev_list_entry *

udev_list_entry_get_next

struct udev_list_entry *

list_entry

struct udev_list_entry *

udev_list_entry_get_by_name

struct udev_list_entry *

list_entry

const char *

name

const char *

udev_list_entry_get_name

struct udev_list_entry *

list_entry

const char *

udev_list_entry_get_value

struct udev_list_entry *

list_entry

Return Value

On success, `udev_list_entry_get_next()` and `udev_list_entry_get_by_name()` return a pointer to the requested list entry. If no such entry can be found, or on failure, `NULL` is returned.

On success, `udev_list_entry_get_name()` and `udev_list_entry_get_value()` return a pointer to a constant string representing the requested value. The string is bound to the lifetime of the list entry itself. On failure, `NULL` is returned.

History

`udev_list_entry_get_next()`, `udev_list_entry_get_by_name()`, `udev_list_entry_get_name()`, and `udev_list_entry_get_value()` were added in version 221.

See Also

`udev_new(3)`, `udev_device_new_from_syspath(3)`, `udev_enumerate_new(3)`, `udev_monitor_new_from_netlink(3)`, `systemd(1)`

□□□ #2
□ □□□ □□□ 2026-10-31 15:08:27 UTC
□ □□□ □□□ 2026-10-31 15:08:28 UTC