cluster-addslotsrange

□□

- Example
- Usage in Valkey Cluster

The `CLUSTER ADDSLOTSRANGE` is similar to the `CLUSTER ADDSLOTS` command in that they both assign hash slots to nodes.

The difference between the two commands is that `CLUSTER ADDSLOTS` takes a list of slots to assign to the node, while `CLUSTER ADDSLOTSRANGE` takes a list of slot ranges (specified by start and end slots) to assign to the node.

Example

To assign slots 1 2 3 4 5 to the node, the `CLUSTER ADDSLOTS` command is:

```
> CLUSTER ADDSLOTS 1 2 3 4 5
OK
```

The same operation can be completed with the following `CLUSTER ADDSLOTSRANGE` command:

```
> CLUSTER ADDSLOTSRANGE 1 5
OK
```

Usage in Valkey Cluster

This command only works in cluster mode and is useful in the following Valkey Cluster operations:

1. To create a new cluster, `CLUSTER ADDSLOTSRANGE` is used to initially set up primary nodes splitting the available hash slots among them.
2. In order to fix a broken cluster where certain slots are unassigned.

□□□ #1
□ □□□ □□□ 2026-10-31 15:11:24 UTC
□ □□□ □□□ 2026-10-31 15:11:24 UTC