给定一个空目录

目录

- 使用方法
- 相关

创建一个空目录。

使用方法

```
场景：我的示例场景

  给定一个空目录

  ...
```

Behat 步骤文档在每次发布时从 *WP-CLI* 代码库生成。如需改进，请提交拉取请求。

相关

- **Given /^an? (empty|non-existent) ([^\s]+) directory$/** - 创建或删除指定目录。
- **Given an empty cache** - 清空 WP-CLI 缓存目录。
- **Given /^an? ([^\s]+) (file|cache file):$/** - 创建包含指定内容的文件。
- **Given /^"([^"]+)" replaced with "([^"]+)" in the ([^\s]+) file$/** - 使用正则表达式在文件中搜索并替换字符串。
- **Given /^that HTTP requests to (.*?) will respond with:$/** - 模拟对指定 URL 的 HTTP 请求。
- **Given WP files** - 下载 WordPress 文件但不安装。
- **Given wp-config.php** - 使用 `wp config create` 创建 wp-config.php 文件。
- **Given a database** - 创建空数据库。
- **Given a WP install(ation)** - 安装 WordPress。
- **Given a WP install(ation) in :subdir** - 在指定目录中安装 WordPress。

- **Given a WP install(ation) with Composer** - □□ Composer □□ WordPress□
- **Given a WP install(ation) with Composer and a custom vendor directory :vendor_directory** - □□ Composer □□□□□□□□□□ WordPress□
- **Given /^a WP multisite (subdirectory|subdomain)?\s?(install|installation)$/** - □□ WordPress □□□□
- **Given these installed and active plugins:** - □□□□□□□□□□□□□
- **Given a custom wp-content directory** - □□□□□□□□ `wp-content` □□□
- **Given download:** - □□□□□□□□□□□□□□□
- **Given /^save (STDOUT|STDERR) ([\'].+[^\'])?\s?as \{(\w+)\}$/** - □ STDOUT □ STDERR □□□□□□□□□□
- **Given /^a new Phar with (?:the same version|version "([^"]+)")$/** - □□□□□□□□□□□ WP-CLI Phar □□□
- **Given /^a downloaded Phar with (?:the same version|version "([^"]+)")$/** - □ GitHub □□□□□□□ WP-CLI Phar □□□
- **Given /^save the (.+) file ([\'].+[^\'])?as \{(\w+)\}$/** - □□□□□□□□□□□□□□□
- **Given a misconfigured WP_CONTENT_DIR constant directory** - □□ wp-config.php □□□□ `WP_CONTENT_DIR` □□□□□□□□
- **Given a dependency on current wp-cli** - □ `wp-cli/wp-cli` □□□ Composer □□□□
- **Given a PHP built-in web server** - □□□□□□□□□ PHP □□ Web □□□□
- **Given a PHP built-in web server to serve :subdir** - □□□□□□□□□□□ PHP □□ Web □□□□

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC