文档标准

目录

命令注解
类注释
Messages within command execution
命令参数说明

为促进 WP-CLI
命令间的统一性与一致性，我们制定了这些文档标准并鼓励您遵循。通用性是可用性的关键要素，因为它能降低在不同命令间切换时所需的认知负荷。

针对 WP-CLI 项目的拉取请求将依据这些标准进行审核。也请为您自定义的命令遵循这些标准。

命令注解

以下是 wp cron event schedule 命令的 PHPdoc 注解示例：

/**
* 安排新的 cron 事件。

*

* ## 选项

*

* <hook>
* : 钩子名称。

*

* [<next-run>]
* : Unix 时间戳或与 `strtotime()` 兼容的英文文本日期时间描述。默认为当前时间。

*

* [<recurrence>]
* : 事件应重复的频率。可用计划名称请参见 `wp cron schedule list`。默认为不重复。

*

* [--<field>=<value>]
* : 事件的关联参数。

*

```
 * ## □□
 *
 *     # □□□□ cron □□□
 *     $ wp cron event schedule cron_test
 *     Success: Scheduled event with hook 'cron_test' for 2016-05-31 10:19:16 GMT.
 *
 *     # □□□□□□□□□□ cron □□□
 *     $ wp cron event schedule cron_test now hourly
 *     Success: Scheduled event with hook 'cron_test' for 2016-05-31 10:20:32 GMT.
 *
 *     # □□□□ cron □□□□□□□□□□□
 *     $ wp cron event schedule cron_test '+1 hour' --foo=1 --bar=2
 *     Success: Scheduled event with hook 'cron_test' for 2016-05-31 11:21:35 GMT.
 */
```

□□□□□□□□

- "□□□□ cron □□□ " □□□□□□□□□□□□□□□ 50 □□□□□□□□□□□□□□□□□□□□□□□□
- □□□□□□□ `## □□` □□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□
- □□□□□□□ `## □□` □□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
- □□□□□□□□ 3 □□□□
  - □□
    - □□□ `#` □□□□□□□
    - □□□□□□□□□□□□□
    - □□□□□□□□□□□□□□□□□□□□
    - □□□ `# □□□□□□□`
  - □□
    - □□□ `$` □□□□□□□□□□ `$ wp db create`
  - □□□□
    - □□□□□□□□□□□□□□□□□□□□

```
/**
 * □□□□□
 *
 * ## □□
 *
 *     # □□□□ URL□
 *     $ wp option get siteurl
 *     http://example.com
 *
 *     # □□□□□
 *     $ wp option add my_option foobar
 *     Success: Added 'my_option' option.
 *
 *     # □□□□□
 *     $ wp option update my_option '{"foo": "bar"}' --format=json
 *     Success: Updated 'my_option' option.
 *
 *     # □□□□□
 *     $ wp option delete my_option
 *     Success: Deleted 'my_option' option.
 */
```

- □□□□□□□□□□□□□□□□□□□□□□□□□□□□

Messages within command execution

```
$ wp theme activate twentysixteen
Success: Switched to 'Twenty Sixteen' theme.
```

- Message must start with a capital letter.
  - Exception: When message starts with a special key and is wrapped with quotes. Eg - `'movie' is not a registered post type.`
- If single line message, it must end with `.`.
  - Exception: There should be no trailing character in the end when colon `:` is used like this. `Invalid ID: 123`
  - Exception: Message to display in progress bar can omit trailing period. Eg - `Generating comments`
- Filenames and folder names must be wrapped with quotes (`'`).
- Roles, sidebar ID, post type key, taxonomy key must be wrapped with quotes.
- Message in the context of ongoing action could end with `...`. Eg - `Downloading from https://github.com/wp-cli/wp-cli/releases/download/v0.23.1/wp-cli-0.23.1.phar...`

命令参数说明

如果命令参数有一组允许的值，我们为默认值和可用选项设置了特殊格式（主要类似于 YAML）。

[--format=<format>]
: 以特定格式渲染输出。

- - -

default: table
options:
- table
- csv

- json
- count

- yaml

- - -

区块以参数描述下方单独一行的 --- 开始。
下一行使用 default: value 指定默认值。
对于选项，在下一行以 options: 开始。
按以下模式列出值： 2 个空格， -， 1 个空格，值以 --- 结束区块。

版本号 #2
由 壳壳虫 创建于 2026-03-26 17:08:46 UTC
由 壳壳虫 更新于 2026-03-26 17:08:46 UTC