wp ability category get

目录
选项
可用字段
示例
GLOBAL PARAMETERS

获取已注册能力类别的详细信息。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考。

<slug> : 类别别名。

[--field=<field>] : 不返回整个类别，而是返回单个字段的值。

[--fields=<fields>] : 将输出限制在特定字段。默认为所有字段。

[--format=<format>] : 以特定格式呈现输出。 --- 默认值: table 选项:

table
csv

json
yaml ---

可用字段

slug
label
description
meta

示例

```
# □□□□□□□□□□□□□□
$ wp ability category get site
+-------------+-------------------------------------------------------+
| Field       | Value                                                 |
+-------------+-------------------------------------------------------+
| slug        | site                                                  |
| label       | Site                                                  |
| description | □□□□□□□□□□□□□□□□□□                    |
| meta        | {}                                                    |
+-------------+-------------------------------------------------------+

# □ JSON □□□□□□□□□□
$ wp ability category get site --format=json
{"slug":"site","label":"Site","description":"...","meta":"{}"}

# □□□□□□□
$ wp ability category get site --field=label
Site
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.

Argument	Description
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC