

wp block binding list



- [OPTIONS](#)
 - [AVAILABLE FIELDS](#)
 - [EXAMPLES](#)
 - [GLOBAL PARAMETERS](#)
-

Lists registered block binding sources.

OPTIONS

See the [argument syntax](#) reference for a detailed explanation of the syntax conventions used.

`[--field=<field>]` : Prints the value of a single field for each source.

`[--fields=<fields>]` : Limit the output to specific source fields.

`[--format=<format>]` : Render output in a particular format. --- default: table options:

- table
- csv
- json
- count
- yaml
- ids ---

AVAILABLE FIELDS

These fields will be displayed by default for each source:

- name
- label

These fields are optionally available:

- uses_context

EXAMPLES

```
# List all binding sources
$ wp block binding list

# Get source names only
$ wp block binding list --field=name

# Export sources to JSON
$ wp block binding list --format=json
```

GLOBAL PARAMETERS

These [global parameters](#) have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
<code>--path=<path></code>	Path to the WordPress files.
<code>--url=<url></code>	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
<code>--ssh=[<scheme>:][<user>@]<host container>[:<port>][<path>]</code>	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
<code>--http=<http></code>	Perform operation against a remote WordPress installation over HTTP.
<code>--user=<id login email></code>	Set the WordPress user.
<code>--skip-plugins[=<plugins>]</code>	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
<code>--skip-themes[=<themes>]</code>	Skip loading all themes, or a comma-separated list of themes.
<code>--skip-packages</code>	Skip loading all installed packages.
<code>--require=<path></code>	Load PHP file before running the command (may be used more than once).
<code>--exec=<php-code></code>	Execute PHP code before running the command (may be used more than once).
<code>--context=<context></code>	Load WordPress in a given context.
<code>--[no-]color</code>	Whether to colorize the output.

Argument	Description
--debug[=<group>]	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
--prompt[=<assoc>]	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
--quiet	Suppress informational messages.

#2

2026-03-26 17:08:46 UTC

2026-03-26 17:08:46 UTC