wp cli check-update

目录
OPTIONS
示例
GLOBAL PARAMETERS

检查是否有可用的 WP-CLI 新版本。

此命令在 before_wp_load 钩子上运行，恰好在 WP 加载过程开始之前。

查询 GitHub 发布 API。如果有可用更新则返回可用版本，如果使用最新版本则返回成功消息。

OPTIONS

请参阅 参数语法 参考，以详细了解所使用的语法约定。

[--patch] : 仅列出补丁更新。

[--minor] : 仅列出次要更新。

[--major] : 仅列出主要更新。

[--field=<field>] : 为每个更新打印单个字段的值。

[--fields=<fields>] : 将输出限制为特定的对象字段。默认为 version,update_type,package_url,status,requires_php。

[--format=<format>] : 以特定格式呈现输出。 --- 默认值: table 选项:

table
csv

json
count

yaml ---

示例

```
# □□□□□□
$ wp cli check-update
Success: WP-CLI □□□□□□□□

# □□□□□□□□□□□□□□□
$ wp cli check-update
+---------+-------------
+-------------------------------------------------------------------------------+
| version | update_type |
package_url                                                                     |
+---------+-------------
+-------------------------------------------------------------------------------+
| 0.24.1  | patch       | https://github.com/wp-cli/wp-cli/releases/download/v0.24.1/wp-cli-
0.24.1.phar |
+---------+-------------
+-------------------------------------------------------------------------------+
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).

Argument	Description
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC