wp comment list

目录
OPTIONS
可用字段
示例
GLOBAL PARAMETERS

获取评论列表。

基于 WP_Comment_Query()支持的所有参数显示评论。

OPTIONS

请参阅 参数语法 参考，了解所用语法约定的详细说明。

[--<field>=<value>] : 传递给 WP_Comment_Query 的一个或多个参数。

[--field=<field>] : 为每条评论打印单个字段的值。

[--fields=<fields>] : 将输出限制为特定的对象字段。

[--format=<format>] : 以特定格式呈现输出。 --- 默认值: table 选项:

table
ids
csv

json
count

yaml ---

可用字段

默认情况下，每条评论将显示以下字段：

comment_ID
comment_post_ID

- comment_date
- comment_approved
- comment_author
- comment_author_email

□□□□□□□□□□

- comment_author_url
- comment_author_IP
- comment_date_gmt
- comment_content
- comment_karma
- comment_agent
- comment_type
- comment_parent
- user_id
- url

□□

```
# □□□□ ID□
$ wp comment list --field=ID
22
23
24

# □□□□□□□□□□□
$ wp comment list --post_id=1 --fields=ID,comment_date,comment_author
+------------+---------------------+----------------+
| comment_ID | comment_date        | comment_author |
+------------+---------------------+----------------+
| 1          | 2015-06-20 09:00:10 | Mr WordPress   |
+------------+---------------------+----------------+

# □□□□□□□□□□
$ wp comment list --number=3 --status=approve --fields=ID,comment_date,comment_author
+------------+---------------------+----------------+
| comment_ID | comment_date        | comment_author |
+------------+---------------------+----------------+
| 1          | 2015-06-20 09:00:10 | Mr WordPress   |
| 30         | 2013-03-14 12:35:07 | John Doe       |
```

```
| 29         | 2013-03-14 11:56:08 | Jane Doe       |
+------------+---------------------+----------------+

# □□□□□□□□□□
$ wp comment list --number=3 --status=hold --fields=ID,comment_date,comment_author
+------------+---------------------+----------------+
| comment_ID | comment_date        | comment_author |
+------------+---------------------+----------------+
| 8          | 2023-11-10 13:13:06 | John Doe       |
| 7          | 2023-11-10 13:09:55 | Mr WordPress   |
| 9          | 2023-11-10 11:22:31 | Jane Doe       |
+------------+---------------------+----------------+

# □□□□□□□□□□□□
$ wp comment list --status=spam --fields=ID,comment_date,comment_author
+------------+---------------------+----------------+
| comment_ID | comment_date        | comment_author |
+------------+---------------------+----------------+
| 2          | 2023-11-10 11:22:31 | Jane Doe       |
+------------+---------------------+----------------+

# □□□□□□□□□□□
$ wp comment list --status=trash --fields=ID,comment_date,comment_author
+------------+---------------------+----------------+
| comment_ID | comment_date        | comment_author |
+------------+---------------------+----------------+
| 3          | 2023-11-10 11:22:31 | John Doe       |
+------------+---------------------+----------------+
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.

Argument	Description
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC