wp core verify-checksums

目录
OPTIONS

示例
GLOBAL PARAMETERS

验证 WordPress 文件与 WordPress.org 校验和的一致性。

此命令在 before_wp_load 钩子上运行，恰好在 WordPress 加载过程开始之前。

从 WordPress.org 下载当前版本的 md5 校验和，并与当前已安装的文件进行比较。

出于安全考虑，验证校验和时避免加载 WordPress。

如果使用此命令验证时遇到问题，请确保根据网站管理区域 仪表盘->更新 菜单中的值传递相应的 --locale 和 -- version 参数。

OPTIONS

请参阅 参数语法 参考，了解所用语法约定的详细说明。

[--include-root] : 验证根目录中的所有文件和文件夹，如果发现任何非 WordPress 项目则发出警告。

[--version=<version>] : 针对特定版本的 WordPress 验证校验和。

[--locale=<locale>] : 针对特定区域设置的 WordPress 验证校验和。

[--insecure] : 如果 TLS
握手失败，则在不进行证书验证的情况下重试下载。注意：这会使请求容易受到中间人攻击。

[--exclude=<files>] : 从校验和验证中排除特定文件。提供以逗号分隔的文件路径列表。

[--format=<format>] : 以特定格式呈现输出。提供此选项时，消息将以所选格式显示。 --- 默认值: plain 选项:

plain
table
json

- csv
- yaml
- count ---

□□

```
# □□□□□□
$ wp core verify-checksums
□□□WordPress □□□□□□□□□□□□

# □□□□□ WordPress □□□□□□□
$ wp core verify-checksums --version=4.0
□□□WordPress □□□□□□□□□□□□

# □□□□□□□□□□□□□□□
$ wp core verify-checksums --locale=en_US
□□□WordPress □□□□□□□□□□□□

# □□□□□□□□□□□□□□□
$ wp core verify-checksums --locale=ja
□□□□□□□□□□□□□□□□□wp-includes/version.php
□□□□□□□□□□□□□□□□□readme.html
□□□□□□□□□□□□□□□□□wp-config-sample.php
□□□WordPress □□□□□□□□□□□□

# □□□□□□□□□□□□
$ wp core verify-checksums --exclude="readme.html"
□□□WordPress □□□□□□□□□□□□

# □□□□□□□□□□□□□□□
$ wp core verify-checksums --format=json
[{"file":"readme.html","message":"File doesn't verify against checksum"}]
□□□WordPress □□□□□□□□□□□□□
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC