wp db query

目录

- OPTIONS
- 示例
- 多站点使用说明
- GLOBAL PARAMETERS

对数据库执行 SQL 查询。

此命令在 `after_wp_config_load` 钩子上运行，在 wp-config.php 加载到作用域之后。

使用 wp-config.php 中指定的 `DB_HOST`、`DB_NAME`、`DB_USER` 和 `DB_PASSWORD` 数据库凭据执行任意 SQL 查询。

使用 `--skip-column-names` MySQL 参数从 SELECT 查询中排除表头。通过管道传输输出来完全移除 ASCII 表格。

OPTIONS

请参阅 参数语法 参考，以详细了解所使用的语法约定。

[<sql>]：一条 SQL 查询语句。如果未提供，将尝试从 STDIN 读取。

[--dbuser=<value>]：传递给 mysql 的用户名。默认为 DB_USER。

[--dbpass=<value>]：传递给 mysql 的密码。默认为 DB_PASSWORD。

[--<field>=<value>]：传递给 mysql 的额外参数。请参阅 mysql 文档。

[--defaults]：加载环境的 MySQL 选项文件。默认行为是跳过加载它们，以避免因配置错误而导致失败。

示例

```
# 执行存储在文件中的查询
$ wp db query < debug.sql
```

```
# 查询数据库中的特定值（通过管道移除 ASCII 表格边框）
$ wp db query 'SELECT option_value FROM wp_options WHERE option_name="home"' --skip-column-
names
+---------------------+
| https://example.com |
+---------------------+

# 检查数据库中的所有表
$ wp db query "CHECK TABLE $(wp db tables | paste -s -d, -);"
+--------------------------------------+-------+----------+----------+
| Table                                | Op    | Msg_type | Msg_text |
+--------------------------------------+-------+----------+----------+
| wordpress_dbase.wp_users             | check | status   | OK       |
| wordpress_dbase.wp_usermeta          | check | status   | OK       |
| wordpress_dbase.wp_posts             | check | status   | OK       |
| wordpress_dbase.wp_comments          | check | status   | OK       |
| wordpress_dbase.wp_links             | check | status   | OK       |
| wordpress_dbase.wp_options           | check | status   | OK       |
| wordpress_dbase.wp_postmeta          | check | status   | OK       |
| wordpress_dbase.wp_terms             | check | status   | OK       |
| wordpress_dbase.wp_term_taxonomy     | check | status   | OK       |
| wordpress_dbase.wp_term_relationships | check | status   | OK       |
| wordpress_dbase.wp_termmeta          | check | status   | OK       |
| wordpress_dbase.wp_commentmeta       | check | status   | OK       |
+--------------------------------------+-------+----------+----------+

# 将额外参数传递给 MySQL
$ wp db query 'SELECT * FROM wp_options WHERE option_name="home"' --skip-column-names
+---+------+-----------------------------+-----+
| 2 | home | http://wordpress-develop.dev | yes |
+---+------+-----------------------------+-----+
```

多站点使用说明

请注意，全局 `--url` 参数对此命令无效。如需查询主站点之外其他站点的数据，您需要手动修改表名，使用包含站点 ID 的前缀。

例如，要获取第二个站点的 `home` 选项值，请按如下方式修改上述示例：

```
$ wp db query 'SELECT option_value FROM wp_2_options WHERE option_name="home"' --skip-column-
names
+----------------------+
| https://example2.com |
+----------------------+
```

□□□□□□□□ ID□□□□ `wp site list` □□□

```
# wp site list --fields=blog_id,url
+---------+----------------------+
| blog_id | url                  |
+---------+----------------------+
| 1       | https://example1.com/ |
| 2       | https://example2.com/ |
+---------+----------------------+
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).

Argument	Description
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC