wp db size

目录

选项

示例
GLOBAL PARAMETERS

显示数据库名称和大小。

显示 wp-config.php 中指定的 DB_NAME 的数据库名称和大小。默认以人类可读的数字显示大小。

可用的尺寸格式包括：

b (字节)
kb (千字节)
mb (兆字节)
gb (吉字节)
tb (太字节)
B (ISO 字节设置，无转换 )
KB (ISO 千字节设置， 1 KB = 1,000 B)
KiB (ISO 千二进制字节设置， 1 KiB = 1,024 B) MB (ISO 兆字节设置， 1 MB = 1,000 KB)
MiB (ISO 兆二进制字节设置， 1 MiB = 1,024 KiB) GB (ISO 吉字节设置， 1 GB = 1,000 MB)
GiB (ISO 吉二进制字节设置， 1 GiB = 1,024 MiB)
TB (ISO 太字节设置， 1 TB = 1,000 GB)
TiB (ISO 太二进制字节设置， 1 TiB = 1,024 GiB)

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考文档。

[--size_format=<format>] : 仅显示数据库大小，为一个纯数字。 --- 选项:

b
kb
mb
gb

tb
B
KB
KiB
MB
MiB
GB
GiB
TB
TiB ---

[--tables] : 显示每个表名及其大小，而不是数据库总大小。

[--human-readable] : 以人类可读的格式显示数据库大小。

[--format=<format>] : 以特定格式渲染输出。 --- 选项:

table
csv

json
yaml ---

[--scope=<scope>] : 可以是 all、global、ms_global、blog 或 old。默认为 all。

[--network] : 列出多站点安装中的所有表。

[--decimals=<decimals>] : 小数点后的位数。默认为 0。

[--all-tables-with-prefix] : 列出所有匹配表前缀的表，即使未在 $wpdb 中注册。会覆盖 --network 选项。

[--all-tables] : 列出数据库中的所有表，无论前缀如何，即使未在 $wpdb 中注册。会覆盖 --all-tables-with-prefix 选项。

[--order=<order>] : 升序或降序排列。 --- 默认值: asc 选项:

asc

desc ---

[--orderby=<orderby>] : 按字段排序。 --- 默认值: name 选项:

name

size ---

示例

```
$ wp db size
+------------------+------+
| □□               | □□ |
+------------------+------+
| wordpress_default | 6 MB |
+------------------+------+

$ wp db size --tables
+-----------------------+-------+
| □□                    | □□  |
+-----------------------+-------+
| wp_users              | 64 KB |
| wp_usermeta           | 48 KB |
| wp_posts              | 80 KB |
| wp_comments           | 96 KB |
| wp_links              | 32 KB |
| wp_options            | 32 KB |
| wp_postmeta           | 48 KB |
| wp_terms              | 48 KB |
| wp_term_taxonomy      | 48 KB |
| wp_term_relationships | 32 KB |
| wp_termmeta           | 48 KB |
| wp_commentmeta        | 48 KB |
+-----------------------+-------+

$ wp db size --size_format=b
5865472

$ wp db size --size_format=kb
5728

$ wp db size --size_format=mb
6
```

# GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

| Argument | Description |
|---|---|

| | |
|---|---|
| `--path=<path>` | Path to the WordPress files. |
| `--url=<url>` | Pretend request came from given URL. In multisite, this argument is how the target site is specified. |
| `--ssh=[<scheme>:][<user>@]<host\|container>[:<port>][<path>]` | Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant"). |
| `--http=<http>` | Perform operation against a remote WordPress installation over HTTP. |
| `--user=<id\|login\|email>` | Set the WordPress user. |
| `--skip-plugins[=<plugins>]` | Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded. |
| `--skip-themes[=<themes>]` | Skip loading all themes, or a comma-separated list of themes. |
| `--skip-packages` | Skip loading all installed packages. |
| `--require=<path>` | Load PHP file before running the command (may be used more than once). |
| `--exec=<php-code>` | Execute PHP code before running the command (may be used more than once). |
| `--context=<context>` | Load WordPress in a given context. |
| `--[no-]color` | Whether to colorize the output. |
| `--debug[=<group>]` | Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help. |
| `--prompt[=<assoc>]` | Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values. |
| `--quiet` | Suppress informational messages. |

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC