wp find

目录
OPTIONS
可用字段
示例
GLOBAL PARAMETERS

在文件系统中查找 WordPress 安装。

此命令在 before_wp_load 钩子上运行，恰好在 WP 加载过程开始之前。

递归遍历提供的 <path> 子目录以查找并报告 WordPress 安装。 WordPress 安装是指包含 version.php 文件的 wp-includes 目录。

避免递归某些已知路径（例如 /node_modules/、隐藏系统目录）以显著提升性能。

显示找到 WordPress 安装的深度及其别名（如果存在）。

OPTIONS

请参阅 参数语法 参考，以详细了解所使用的语法约定。

<path> : 要搜索其子目录的路径。

[--skip-ignored-paths] : 跳过默认情况下被忽略的路径。

[--include_ignored_paths=<paths>] : 以 CSV 格式包含额外的被忽略路径（例如 '/sys-backup/,/temp/' ）。

[--max_depth=<max-depth>] : 仅递归到指定的深度（包含该深度）。

[--fields=<fields>] : 将输出限制为特定的行字段。

[--field=<field>] : 为每一行输出一个特定的字段。

[--format=<format>] : 以特定格式呈现输出。 --- 默认值: table 选项:

table

- json
- csv
- yaml
- count ---

[--verbose] : □□□□□□□□□ STDOUT□

## □□□

□□□□□□□□□□□□□□□□

- version_path - version.php □□□□□□
- version - WordPress □□□
- depth - □□□□□□□□□□
- alias - WP-CLI □□□□□□□□□□

□□□□□□□□□□

- wp_path - □□□□ `--path=<path>` □□□□□□□□
- db_host - □□□□□□□□
- db_user - □□□□□□□□
- db_name - □□□□□□□□

## □□

```
# □□ WordPress □□□
$ wp find ./
+-------------------------------------+--------------------+-------+--------+
| version_path                        | version            | depth | alias  |
+-------------------------------------+--------------------+-------+--------+
| /Users/wpcli/wp-includes/version.php | 4.8-alpha-39357-src | 2     | @wpcli |
+-------------------------------------+--------------------+-------+--------+
```

# GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

| Argument | Description |
|---|---|
| `--path=<path>` | Path to the WordPress files. |

| Argument | Description |
| --- | --- |
| `--url=<url>` | Pretend request came from given URL. In multisite, this argument is how the target site is specified. |
| `--ssh=[<scheme>:][<user>@]<host\|container>[:<port>][<path>]` | Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant"). |
| `--http=<http>` | Perform operation against a remote WordPress installation over HTTP. |
| `--user=<id\|login\|email>` | Set the WordPress user. |
| `--skip-plugins[=<plugins>]` | Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded. |
| `--skip-themes[=<themes>]` | Skip loading all themes, or a comma-separated list of themes. |
| `--skip-packages` | Skip loading all installed packages. |
| `--require=<path>` | Load PHP file before running the command (may be used more than once). |
| `--exec=<php-code>` | Execute PHP code before running the command (may be used more than once). |
| `--context=<context>` | Load WordPress in a given context. |
| `--[no-]color` | Whether to colorize the output. |
| `--debug[=<group>]` | Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help. |
| `--prompt[=<assoc>]` | Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values. |
| `--quiet` | Suppress informational messages. |

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC