wp language plugin update

- OPTIONS
- EXAMPLES
- GLOBAL PARAMETERS

Updates installed languages for one or more plugins.

OPTIONS

See the argument syntax reference for a detailed explanation of the syntax conventions used.

[<plugin>...] : One or more plugins to update languages for.

[--all] : If set, languages for all plugins will be updated.

[--dry-run] : Preview which translations would be updated.

EXAMPLES

```
# Update all installed language packs for all plugins.
$ wp language plugin update --all
Updating 'Japanese' translation for Akismet 3.1.11...
Downloading translation from
https://downloads.wordpress.org/translation/plugin/akismet/3.1.11/ja.zip...
Translation updated successfully.
Success: Updated 1/1 translation.
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description

`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC