wp option set

□□

- □□
- □□
- GLOBAL PARAMETERS

□□□□□□

□□ `wp option update` □□□□□□

□□

□□□□□□□□□□□□□□□□□□ □□□□ □□□

<key> : □□□□□□□□□

[<value>] : □□□□□□□□□□ STDIN □□□□

[--autoload=<autoload>] : □□ WordPress 4.2 □□□□□□□□□□□□□□□□□□□□ --- □□ :

- 'on'
- 'off'
- 'yes'
- 'no' ---

[--format=<format>] : □□□□□□□□ --- □□□ : plaintext □□ :

- plaintext
- json ---

□□

```
# □□□□□□□□□□□□□□□
$ wp option update my_option < value.txt
Success: Updated 'my_option' option.
```

```
# □□ xargs □□□□□□□□□□□□□□□
$ wp site list --field=url | xargs -n1 -I {} sh -c 'wp --url={} option update my_option
my_value'
Success: Updated 'my_option' option.
Success: Updated 'my_option' option.

# □□□□□□□□□□
$ wp option update blogname "Random blog name"
Success: Updated 'blogname' option.

# □□□□□□□□□□
$ wp option update blogdescription "Some random blog description"
Success: Updated 'blogdescription' option.

# □□□□□□□□□□□□□
$ wp option update admin_email someone@example.com
Success: Updated 'admin_email' option.

# □□□□□□□□
$ wp option update default_role author
Success: Updated 'default_role' option.

# □□□□□□□□□
$ wp option update timezone_string "America/New_York"
Success: Updated 'timezone_string' option.
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").

Argument	Description
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC