wp package browse

目录
OPTIONS

可用字段
示例
GLOBAL PARAMETERS

浏览可供安装的 WP-CLI 软件包。

此命令在 before_wp_load 钩子上运行，恰好在 WP 加载过程开始之前。

列出可从 软件包索引
安装的软件包。尽管出于向后兼容性考虑，软件包索引将继续保留，但它已被弃用且不再更新。请参阅 https://github.com/wp-cli/ideas/issues/51 了解其潜在替代方案。

OPTIONS

请参阅 参数语法 参考，以详细了解所使用的语法约定。

[--fields=<fields>] : 将输出限制在特定字段。默认为所有字段。

[--format=<format>] : 以特定格式呈现输出。 --- 默认值: table 选项:

table
csv

ids
json
yaml ---

可用字段

默认情况下，每个包将显示以下字段：

name（名称）
description（描述）
authors（作者）

- version□□□□

□□□□□□□

□□

```
$ wp package browse --format=yaml
---
10up/mu-migration:
  name: 10up/mu-migration
  description: □□ WP-CLI □□□□□□□□□□ WordPress □□□□□□□□□
  authors: Nícholas André
  version: dev-main, dev-develop
aaemnnosttv/wp-cli-dotenv-command:
  name: aaemnnosttv/wp-cli-dotenv-command
  description: WP-CLI □ Dotenv □□
  authors: Evan Mattson
  version: v0.1, v0.1-beta.1, v0.2, dev-main, dev-dev, dev-develop, dev-tests/behat
aaemnnosttv/wp-cli-http-command:
  name: aaemnnosttv/wp-cli-http-command
  description: □□ WordPress HTTP API □ WP-CLI □□
  authors: Evan Mattson
  version: dev-main
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.

Argument	Description
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC