wp plugin activate

□□

- □□
- □□
- GLOBAL PARAMETERS

□□□□□□□□□□

□□

□□□□□□□□□□□□□□□□□□□□ □□□□ □□□□□

[<plugin>...] : □□□□□□□□□□□□

[--all] : □□□□□□□□□□□□□□

[--exclude=<name>] : □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

[--network] : □□□□□□□□□□□□□□□□□□□□□□

□□

```
# □□□□□
$ wp plugin activate hello
□□ 'hello' □□□□□
□□□□□□□ 1 □□□□□□ 1 □□

# □□□□□□□□□□□□□□□□□
$ wp plugin activate hello --network
□□ 'hello' □□□□□□□□□
□□□□□□□□□□□ 1 □□□□□□ 1 □□

# □□□□□□□□□□□□
$ wp plugin activate $(wp plugin list --recently-active --field=name)
```

```
□□ 'bbpress' □□□□
□□ 'buddypress' □□□□
□□□□□□ 2 □□□□□ 2 □□

# □□□□□□□□□□□□□□□□□
$ wp plugin activate $(wp plugin list --recently-active --field=name) --network
□□ 'bbpress' □□□□□□□□
□□ 'buddypress' □□□□□□□□
□□□□□□ 2 □□□□□ 2 □□
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.

Argument	Description
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC