wp plugin install

目录

选项
EXAMPLES
GLOBAL PARAMETERS

安装一个或多个插件。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考。

<插件 |zip|url>... : 要安装的一个或多个插件。接受插件别名、本地 zip 文件路径或远程 zip 文件的 URL。

[--version=<版本 >] : 如果设置，则从 wordpress.org 获取该特定版本，而非稳定版本。

[--force] : 如果设置，该命令将覆盖任何已安装的插件版本，而无需确认提示。

[--ignore-requirements] : 如果设置，该命令将安装插件，同时忽略插件作者指定的任何 WordPress 或 PHP 版本要求。

[--activate] : 如果设置，插件将在安装后立即激活。

[--activate-network] : 如果设置，插件将在安装后立即进行网络激活。

[--insecure] : 如果 TLS
握手失败，则在不进行证书验证的情况下重试下载。注意：这会使请求容易受到中间人攻击。

EXAMPLES

# Install the latest version from wordpress.org and activate
$ wp plugin install bbpress --activate
Installing bbPress (2.5.9)
Downloading install package from https://downloads.wordpress.org/plugin/bbpress.2.5.9.zip... Using cached file '/home/vagrant/.wp-cli/cache/plugin/bbpress-2.5.9.zip'...

```
Unpacking the package...
Installing the plugin...
Plugin installed successfully.
Activating 'bbpress'...
Plugin 'bbpress' activated.
Success: Installed 1 of 1 plugins.

# Install the development version from wordpress.org
$ wp plugin install bbpress --version=dev
Installing bbPress (Development Version)
Downloading install package from https://downloads.wordpress.org/plugin/bbpress.zip...
Unpacking the package...
Installing the plugin...
Plugin installed successfully.
Success: Installed 1 of 1 plugins.

# Install from a local zip file
$ wp plugin install ../my-plugin.zip
Unpacking the package...
Installing the plugin...
Plugin installed successfully.
Success: Installed 1 of 1 plugins.

# Install from a remote zip file
$ wp plugin install http://s3.amazonaws.com/bucketname/my-
plugin.zip?AWSAccessKeyId=123&amp;Expires=456&amp;Signature=abcdef
Downloading install package from http://s3.amazonaws.com/bucketname/my-
plugin.zip?AWSAccessKeyId=123&amp;Expires=456&amp;Signature=abcdef
Unpacking the package...
Installing the plugin...
Plugin installed successfully.
Success: Installed 1 of 1 plugins.

# Update from a remote zip file
$ wp plugin install https://github.com/envato/wp-envato-market/archive/master.zip --force
Downloading install package from https://github.com/envato/wp-envato-market/archive/master.zip
Unpacking the package...
Installing the plugin...
Renamed Github-based project from 'wp-envato-market-master' to 'wp-envato-market'.
Plugin updated successfully
```

```
Success: Installed 1 of 1 plugins.

# Forcefully re-install all installed plugins
$ wp plugin install $(wp plugin list --field=name) --force
Installing Akismet (3.1.11)
Downloading install package from https://downloads.wordpress.org/plugin/akismet.3.1.11.zip...
Unpacking the package...
Installing the plugin...
Removing the old version of the plugin...
Plugin updated successfully
Success: Installed 1 of 1 plugins.
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.

Argument	Description
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC