wp plugin list

目录
OPTIONS

可用字段
示例
GLOBAL PARAMETERS

获取插件列表。

显示站点上已安装插件的列表，包括激活状态、是否有可用更新等信息。

使用 --status=dropin 可列出已安装的 dropins（例如 object-cache.php）。

OPTIONS

请参阅 参数语法 参考，详细了解所使用的语法约定。

[--<field>=<value>] : 根据字段值筛选结果。

[--field=<field>] : 为每个插件打印单个字段的值。

[--fields=<fields>] : 将输出限制为特定的对象字段。

[--format=<format>] : 以特定格式渲染输出。 --- 默认值: table 选项:

table
csv
count

json
yaml ---

[--status=<status>] : 按插件状态筛选输出。 --- 选项:

active
active-network
dropin
inactive

- must-use ---

[--skip-update-check] : □□□□□□□□□□□□□□□□

[--recently-active] : □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□

□□□□□□□□□□□□□□□□□□□□

- name□□□□
- status□□□□
- update□□□□
- version□□□□
- update_version□□□□□□
- auto_update□□□□□□

□□□□□□□□□□

- update_package□□□□□
- update_id□□□ ID□
- title□□□□
- description□□□□
- file□□□□
- author□□□□
- tested_up_to□□□□□
- requires□□□□
- requires_php□ PHP□□□
- wporg_status□ WordPress.org□□□
- wporg_last_updated□ WordPress.org□□□□□

□□

```
# □□□□□□□□□□□□□□□□□□□□
$ wp plugin list --status=active --format=json
[{"name":"dynamic-
hostname","status":"active","update":"none","version":"0.4.2","update_version":"","auto_update
":"off"},{"name":"tinymce-
templates","status":"active","update":"none","version":"4.8.1","update_version":"","auto_updat
e":"off"},{"name":"wp-multibyte-
patch","status":"active","update":"none","version":"2.9","update_version":"","auto_update":"of
f"},{"name":"wp-total-
```

```
hacks","status":"active","update":"none","version":"4.7.2","update_version":"","auto_update":"
off"}]

# □□□□□□□□□□□□□□□□
$ wp site list --field=url | xargs -I % wp plugin list --url=%
+---------+----------------+-----------+---------+-----------------+------------+
| name    | status         | update    | version | update_version | auto_update |
+---------+----------------+-----------+---------+----------------+-------------+
| akismet | active-network | none      | 5.3.1   |                | on          |
| hello   | inactive       | available | 1.6     | 1.7.2          | off         |
+---------+----------------+-----------+---------+----------------+-------------+
+---------+----------------+-----------+---------+----------------+-------------+
| name    | status         | update    | version | update_version | auto_update |
+---------+----------------+-----------+---------+----------------+-------------+
| akismet | active-network | none      | 5.3.1   |                | on          |
| hello   | inactive       | available | 1.6     | 1.7.2          | off         |
+---------+----------------+-----------+---------+----------------+-------------+

# □□□□□ WordPress.org □□□□□□□□□□□
$ wp plugin list --fields=name,wporg_status,wporg_last_updated
+--------------------+--------------+--------------------+
| name               | wporg_status | wporg_last_updated |
+--------------------+--------------+--------------------+
| akismet            | active       | 2023-12-11         |
| user-switching     | active       | 2023-11-17         |
| wordpress-importer | active       | 2023-04-28         |
| local              |              |                    |
+--------------------+--------------+--------------------+

# □□□□□□□□□□□□□□□
$ wp plugin list --recently-active --field=name --format=json
["akismet","bbpress","buddypress"]
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.

Argument	Description
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC