wp post generate

目录
选项
示例
GLOBAL PARAMETERS

生成一些文章。

创建指定数量的包含虚拟数据的新文章。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考。

[--count=<数量 >] : 要生成多少篇文章？ --- 默认值: 100 ---

[--post_type=<类型 >] : 生成文章的类型。 --- 默认值: post ---

[--post_status=<状态 >] : 生成文章的状态。 --- 默认值: publish ---

[--post_title=<文章标题 >] : 文章标题。 --- 默认值: ---

[--post_author=<登录名 >] : 生成文章的作者。 --- 默认值: ---

[--post_date=<年-月-日-时-分-秒>] : 文章的日期。默认为当前时间。

[--post_date_gmt=<年-月-日-时-分-秒>] : 文章在 GMT 时区的日期。默认为 --post_date 的值。

[--post_content] : 如果设置，命令将从 STDIN 读取文章内容。

[--max_depth=<数字 >] : 对于分层文章类型，生成子文章到特定深度。 --- 默认值: 1 ---

[--format=<格式 >] : 以特定格式渲染输出。 --- 默认值: progress 选项:

progress
ids ---

□□

```
# □□□□□□
$ wp post generate --count=10 --post_type=page --post_date=1999-01-04
□□□□□□□  100% [=============================================] 0:01 / 0:04

# □□□□□□□□□□□□□□□
$ curl -N https://loripsum.net/api/5 | wp post generate --post_content --count=10
  % □□    % □□□ % □□□   □□□□   □□    □□     □□    □□
                                □□  □□   □□   □□    □□   □□
100  2509  100  2509    0     0    616      0  0:00:04  0:00:04 --:--:--   616
□□□□□□□  100% [=============================================] 0:01 / 0:04

# □□□□□□□□□□□□□□□□
$ wp post generate --format=ids | xargs -d ' ' -I % wp post meta add % foo bar
□□□□□□□□□□□□□□
□□□□□□□□□□□□□□
□□□□□□□□□□□□□□
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.

Argument	Description
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC