wp profile eval

目录
选项
示例
GLOBAL PARAMETERS

分析任意代码的执行情况。

代码执行发生在 WordPress 完全加载之后，这意味着您可以使用 WordPress 、活动插件或当前主题中定义的任何实用工具。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考。

<php-code> : 要执行的代码，以字符串形式提供。

[--hook[=<hook>]] : 关注所有钩子的关键指标，或特定钩子上的回调函数。

[--fields=<fields>] : 显示一个或多个字段。

[--format=<format>] : 以特定格式渲染输出。 --- 默认值: table 选项:

table
json
yaml

csv ---

[--order=<order>] : 升序或降序排列。 --- 默认值: ASC 选项:

ASC
DESC ---

[--orderby=<fields>] : 设置按哪个字段排序。

示例

```
# □□□□□□□□□ HTTP □□□□□□□
$ wp profile eval 'wp_remote_get( "https://www.apple.com/" );' --
fields=time,cache_ratio,request_count
+---------+-------------+---------------+
| time    | cache_ratio | request_count |
+---------+-------------+---------------+
| 0.1009s | 100%        | 1             |
+---------+-------------+---------------+
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.

Argument	Description
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC