wp scaffold plugin-tests

目录
环境配置
选项说明
EXAMPLES
GLOBAL PARAMETERS

为插件生成运行 PHPUnit 测试所需的文件。

默认生成以下文件：

phpunit.xml.dist 是 PHPUnit 的配置文件。
. circleci/config.yml 是 CircleCI 的配置文件。使用 --ci=<provider> 可选择其他服务。 bin/install-wp-tests.sh 配置 WordPress 测试套件和测试数据库。
tests/bootstrap.php 是在运行测试套件时激活当前插件的文件。
tests/test-sample.php 是包含实际测试的示例文件。
. phpcs.xml.dist 是 PHP_CodeSniffer 规则的集合。

了解更多信息，请参阅 插件单元测试文档 。

环境配置

tests/bootstrap.php 文件会查找 WP_TESTS_DIR 环境变量。

选项说明

关于所用语法约定的详细解释，请参阅 参数语法 参考文档。

[<plugin>] : 要为其生成测试文件的插件名称。

[--dir=<dirname>] : 为非标准插件路径生成测试文件。如果未指定插件别名，则使用目录名。

[--ci=<provider>] : 为持续集成服务商选择配置文件。 --- 默认值: circle 可选值:

circle
gitlab

- bitbucket
- github ---

[--force] : □□□□□□□□□

EXAMPLES

```
# Generate unit test files for plugin 'sample-plugin'.
$ wp scaffold plugin-tests sample-plugin
Success: Created test files.
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.

Argument	Description
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC