wp search-replace

目录
选项
示例
GLOBAL PARAMETERS

在数据库中搜索 /替换字符串。

在选定表的所有行中进行搜索，并将第一个字符串的出现替换为第二个字符串。

默认情况下，该命令使用注册到 $wpdb 对象的表。在多站点环境下，除非指定 --network 参数，否则仅针对当前站点的表。

搜索 /替换功能会智能处理 PHP 序列化数据，且不会更改主键值。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考。

<old> : 要在数据库中搜索的字符串。

<new> : 用此新字符串替换第一个字符串的实例。

[<table>...] : 限制替换操作所针对的数据库表列表。支持通配符，例如 'wp_*options' 或 'wp_post*'。

[--dry-run] : 运行整个搜索 /替换操作并显示报告，但不将更改保存到数据库。

[--network] : 在多站点安装中，对所有注册到 $wpdb 的表进行搜索 /替换。

[--all-tables-with-prefix] : 对任何匹配表前缀的表启用替换，即使它们未在 $wpdb 中注册。

[--all-tables] : 对数据库中的所有表启用替换，无论前缀如何，即使未在 $wpdb 中注册。此选项会覆盖 -- network 和 --all-tables-with-prefix。

[--export[=<file>]] : 将转换后的数据写入 SQL 文件，而不是将替换保存到数据库。如果未提供 <file> ，将输出到 STDOUT。

[--export_insert_size=<rows>] : 定义执行 SQL 导出时单个 INSERT
语句中的行数。您可能需要根据数据库配置更改此值（例如，如果需要减少查询次数）。默认值： 50

[--skip-tables=<tables>] : 不对特定表执行替换。使用逗号分隔多个表。支持通配符，例如 'wp_*options' 或 'wp_post*' 。

[--skip-columns=<columns>] : 不对特定列执行替换。使用逗号分隔多个列。

[--include-columns=<columns>] : 对特定列执行替换。使用逗号分隔多个列。

[--precise] : 强制使用 PHP（而非 SQL）进行替换，这种方式更彻底，但速度更慢。

[--recurse-objects] : 启用递归到对象中以替换字符串。默认为 true；传递 --no-recurse-objects 以禁用。

[--verbose] : 在更新行时将其打印到控制台。

[--regex] : 使用正则表达式（无分隔符）运行搜索。警告：使用 --regex 时，搜索替换所需时间将延长约 15-20 倍。

[--regex-flags=<regex-flags>] : 将 PCRE 修饰符传递给正则表达式搜索替换（例如， 'i'
表示不区分大小写）。

[--regex-delimiter=<regex-delimiter>] :
用于正则表达式的分隔符。如果分隔符出现在搜索字符串中，则必须进行转义。默认值为 chr(1) 的结果。

[--regex-limit=<regex-limit>] :
正则表达式每行（或每行每个反序列化数据位）的最大可能替换次数。默认为 -1（无限制）。

[--format=<format>] : 以特定格式呈现输出。 --- default: table options:

table
count ---

[--report] : 生成报告。默认为 true。

[--report-changed-only] : 仅报告已更改的字段。默认值为 false，除非启用日志记录，此时默认值为 true。

[--log[=<文件 >]] : 记录已更改的项目。如果未提供 <文件 > 或为 "-"，将输出到 STDOUT
。警告：会导致显著减速，类似于或比启用 --precise 或 --regex 更慢。

[--before_context=<数量 >] : 对于日志记录，显示旧匹配项和新替换项之前的字符数。默认 40
。未启用日志记录时忽略。

[--after_context=<数量 >] : 对于日志记录，显示旧匹配项和新替换项之后的字符数。默认 40
。未启用日志记录时忽略。

□□

```
# □□□□□□□□□□□□□
$ wp search-replace 'http://example.test' 'http://example.com' --skip-columns=guid

# □□□□/□□□□□□□□□□□□□
$ wp search-replace 'foo' 'bar' wp_posts wp_postmeta wp_terms --dry-run

# □□□□□□□□□□□□□□□□□□□/□□□□□□□□□
$ wp search-replace '\[foo id="([0-9]+)"' '[bar id="\1"' --regex --regex-flags='i'

# □□□□□□□□□□□□□□□□□□□□□□□□□□□
$ wp search-replace --url=example.com example.com example.test 'wp_*options' wp_blogs wp_site
--network

# □□/□□□□□□□ SQL □□□□□□□□□□
$ wp search-replace foo bar --export=database.sql

# Bash □□□□□□□□□ URL □□/□□□□□□□□ URL□□□□□□□□
#!/bin/bash
if $(wp --url=http://example.com core is-installed --network); then
    wp search-replace --url=http://example.com 'http://example.com' 'http://example.test' --
recurse-objects --network --skip-columns=guid --skip-tables=wp_users
else
    wp search-replace 'http://example.com' 'http://example.test' --recurse-objects --skip-
columns=guid --skip-tables=wp_users
fi
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.

Argument	Description
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC