

wp server

□□

- [OPTIONS](#)
- [□□](#)
- [GLOBAL PARAMETERS](#)

□□ PHP □□ Web □□□□□□□□ WordPress □□

□□□□ `before_wp_load` □□□□□□□□ WP □□□□□□□□

□□ `php -S` □□□□□□ WordPress □□□□□□□□ Web □□□□
<<http://php.net/manual/en/features.commandline.webserver.php>>

□□□□□□ PHP □□ Web □□□□□□ `.htaccess` □□□□□□□□□□□□□□□□□□□□ Web
□□□□

OPTIONS

□□ [□□□□](#) □□□□□□□□□□□□□□□□□□□□

`--host=<host>` : □□□□□□□□□□ --- □□□□ localhost ---

`--port=<port>` : □□□□□□□□□□ --- □□□□ 8080 ---

`--docroot=<path>` : □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

`--config=<file>` : □□□□□□ .ini □□□□□□□□□□

□□□□

```
# □□□□□□□□□□□□□□□□ 8080
$ wp server --host=0.0.0.0

PHP 5.6.9 Development Server started at Tue May 24 01:27:11 2016
Listening on http://0.0.0.0:8080
Document root is /
```

Press Ctrl-C to quit.

```
# 80
```

```
$ wp server --host=localhost.localdomain --port=80
```

```
PHP 5.6.9 Development Server started at Tue May 24 01:30:06 2016
```

```
Listening on http://localhost1.localdomain1:80
```

```
Document root is /
```

Press Ctrl-C to quit.

```
# .ini
```

```
$ wp server --config=development.ini
```

```
PHP 7.0.9 Development Server started at Mon Aug 22 12:09:04 2016
```

```
Listening on http://localhost:8080
```

```
Document root is /
```

Press Ctrl-C to quit.

GLOBAL PARAMETERS

These [global parameters](#) have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
<code>--path=<path></code>	Path to the WordPress files.
<code>--url=<url></code>	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
<code>--ssh=[<scheme>:][<user>@]<host container>[:<port>][<path>]</code>	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
<code>--http=<http></code>	Perform operation against a remote WordPress installation over HTTP.
<code>--user=<id login email></code>	Set the WordPress user.
<code>--skip-plugins[=<plugins>]</code>	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
<code>--skip-themes[=<themes>]</code>	Skip loading all themes, or a comma-separated list of themes.
<code>--skip-packages</code>	Skip loading all installed packages.
<code>--require=<path></code>	Load PHP file before running the command (may be used more than once).
<code>--exec=<php-code></code>	Execute PHP code before running the command (may be used more than once).

Argument	Description
--context=<context>	Load WordPress in a given context.
--[no-]color	Whether to colorize the output.
--debug[=<group>]	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
--prompt[=<assoc>]	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
--quiet	Suppress informational messages.

#2

2026-03-26 17:08:46 UTC

2026-03-26 17:08:46 UTC