wp taxonomy get

目录
选项
可用字段
示例
GLOBAL PARAMETERS

获取已注册分类法的详细信息。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考。

<taxonomy> : 分类法别名。

[--field=<field>] : 不返回整个分类法，而是返回单个字段的值。

[--fields=<fields>] : 将输出限制在特定字段。默认为所有字段。

[--format=<format>] : 以特定格式渲染输出。 --- 默认值: table 选项:

table
csv

json
yaml ---

可用字段

以下字段将默认显示于指定的分类法中：

name

label
description
object_type
show_tagcloud
hierarchical

- public
- labels
- cap

□□□□□□□□□□

- count

## □□

```
# □□ `category` □□□□□□□□□□
$ wp taxonomy get category --fields=name,label,object_type
+-------------+------------+
| Field       | Value      |
+-------------+------------+
| name        | category   |
| label       | Categories |
| object_type | ["post"]   |
+-------------+------------+

# □□ 'post_tag' □□□□□□□□□□
$ wp taxonomy get post_tag --field=cap
{"manage_terms":"manage_categories","edit_terms":"manage_categories","delete_terms":"manage_ca
tegories","assign_terms":"edit_posts"}
```

# GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

| Argument | Description |
|---|---|
| `--path=<path>` | Path to the WordPress files. |
| `--url=<url>` | Pretend request came from given URL. In multisite, this argument is how the target site is specified. |
| `--ssh=[<scheme>:][<user>@]<host\|container>[:<port>][<path>]` | Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant"). |
| `--http=<http>` | Perform operation against a remote WordPress installation over HTTP. |
| `--user=<id\|login\|email>` | Set the WordPress user. |

| Argument | Description |
| --- | --- |
| `--skip-plugins[=<plugins>]` | Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded. |
| `--skip-themes[=<themes>]` | Skip loading all themes, or a comma-separated list of themes. |
| `--skip-packages` | Skip loading all installed packages. |
| `--require=<path>` | Load PHP file before running the command (may be used more than once). |
| `--exec=<php-code>` | Execute PHP code before running the command (may be used more than once). |
| `--context=<context>` | Load WordPress in a given context. |
| `--[no-]color` | Whether to colorize the output. |
| `--debug[=<group>]` | Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help. |
| `--prompt[=<assoc>]` | Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values. |
| `--quiet` | Suppress informational messages. |

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC