

wp term meta add

- Options
- [--help](#)
 - [--quiet](#)

Usage

wp

wp term meta add [--help](#) [--quiet](#)

<id> : [--id](#) ID

<key> : [--key](#)

[<value>] : [--value](#) STDIN [--stdin](#)

[--format=<format>] : [--format](#) --- [--format](#) : plaintext [--format](#) :

- plaintext
- json ---

wp

wp [--help](#) WP-CLI WordPress [--help](#)

wp	wp
--path=<path>	WordPress --path
--url=<url>	--url URL --url
--ssh=[<scheme>:][<user>@]<host container>[:<port>][<path>]	--ssh SSH --ssh "docker" "docker-compose" "docker-compose-run" "vagrant" --ssh
--http=<http>	--http HTTP --http WordPress --http
--user=<id login email>	--user WordPress --user

Options	Description
--skip-plugins[=<plugins>]	Do not load the specified plugins. Possible values: all, mu-plugins. Default: all
--skip-themes[=<themes>]	Do not load the specified themes. Possible values: all, default. Default: all
--skip-packages	Do not load any packages
--require=<path>	Require the specified PHP file(s) before running commands. Multiple files should be space-separated.
--exec=<php-code>	Execute the specified PHP code before running commands.
--context=<context>	Run commands in the specified context. Possible values: wp, wordpress, wp-cli. Default: wp
--[no-]color	Enable or disable color output. Default: auto
--debug[=<group>]	Enable debug mode. Possible values: wp, php, wp-cli, bootstrap, commandfactory, help. Default: none
--prompt[=<assoc>]	Specify the prompt string to use for the interactive shell. Default: wp-cli
--quiet	Do not output any progress messages

#2

2026-03-26 17:08:46 UTC
2026-03-26 17:08:46 UTC